

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
 Product name : Fast Wax
 Product code : VC402

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Main use category : Industrial use, Professional use
 Use of the substance/mixture : Cleaning/washing agents and additives

1.3. Details of the supplier of the safety data sheet

Supplier

Valet-Chem Ltd
 Summit Close
 NG17 8GJ Kirkby In Ashfield Nottingham, Nottinghamshire
 United Kingdom
 T T +44 (0) 844 414 0987
info@valetchem.co.uk

Supplier information

Leading Solvents Ireland Ltd
 The Courtyard, Manor House
 3 Church Road
 Malahide, Co.Dubin
 Ireland
 T +353 1 845 7660

1.4. Emergency telephone number

Emergency number : +44 (0) 844 414 0987 (Office hours only)

Country/Area	Organisation	Emergency number
Ireland	National Poisons Information Centre. Beaumont Hospital. PO Box 1297. Beaumont Road 9 Dublin.	+353 1 809 2566 (Healthcare professionals-24/7) +353 1 809 2166 (public, 8am - 10pm, 7/7)
United Kingdom	NHS 111/NHS 24/NHS Direct.	111 0845 4647 or call a doctor

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Skin sensitisation, Category 1 H317
 Specific target organ toxicity – Repeated exposure, Category 2 H373
 Hazardous to the aquatic environment – Chronic Hazard, H412
 Category 3
 Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

See section 11 for toxicological information. See section 9/10 for physicochemical information. See section 12 for environmental information.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS07

GHS08

Signal word (CLP) :

Warning

Fast Wax

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Contains	: Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics, (2-25%); 2-methylisothiazol-3(2H)-one
Hazard statements (CLP)	: H317 - May cause an allergic skin reaction. H373 - May cause damage to organs through prolonged or repeated exposure. H412 - Harmful to aquatic life with long lasting effects.
Precautionary statements (CLP)	: P260 - Do not breathe mist, spray, vapours. P272 - Contaminated work clothing should not be allowed out of the workplace. P273 - Avoid release to the environment. P280 - Wear protective clothing, eye protection, face protection, protective gloves. P302+P352 - IF ON SKIN: Wash with plenty of water. P314 - Get medical advice/attention if you feel unwell. P333+P313 - If skin irritation or rash occurs: Get medical advice/attention. P362+P364 - Take off contaminated clothing and wash it before reuse. P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards

Contains no PBT and/or vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics, (2-25%)	EC-No.: 919-446-0 REACH-no: 01-2119458049-33	$\geq 1 - < 5$	Flam. Liq. 3, H226 STOT SE 3, H336 STOT RE 1, H372 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 EUH066
N-Butanol	CAS-No.: 71-36-3 EC-No.: 200-751-6 EC Index-No.: 603-004-00-6 REACH-no: 01-2119484630-38	$\geq 0.1 - < 1$	Flam. Liq. 3, H226 Acute Tox. 4 (Oral), H302 (ATE=500 mg/kg bodyweight) STOT SE 3, H335 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H336
Monoethylene Glycol substance with national workplace exposure limit(s) (GB, NL); substance with a Community workplace exposure limit	CAS-No.: 107-21-1 EC-No.: 203-473-3 EC Index-No.: 603-027-00-1 REACH-no: 01-2119456816-28	< 0.1	Acute Tox. 4 (Oral), H302 (ATE=500 mg/kg bodyweight) STOT RE 2, H373
Aluminium Oxide substance with national workplace exposure limit(s) (GB)	CAS-No.: 1344-28-1 EC-No.: 215-691-6 REACH-no: 01-2119529248-35	< 0.1	Not classified

Fast Wax

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
2-methylisothiazol-3(2H)-one	CAS-No.: 2682-20-4 EC-No.: 220-239-6 EC Index-No.: 613-326-00-9 REACH-no: 01-2120764690-50	< 0.1	Acute Tox. 2 (Inhalation), H330 (ATE=0.05 mg/l/4h) Acute Tox. 3 (Dermal), H311 (ATE=300 mg/kg bodyweight) Acute Tox. 3 (Oral), H301 (ATE=100 mg/kg bodyweight) Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 (M=10) Aquatic Chronic 1, H410 EUH071

Specific concentration limits:

Name	Product identifier	Specific concentration limits (%)
2-methylisothiazol-3(2H)-one	CAS-No.: 2682-20-4 EC-No.: 220-239-6 EC Index-No.: 613-326-00-9 REACH-no: 01-2120764690-50	(0.0015 ≤ C ≤ 100) Skin Sens. 1A; H317

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Take off contaminated clothing. Wash contaminated clothing before reuse.
First-aid measures after inhalation	: If inhaled, remove to fresh air and keep at rest in a position comfortable for breathing. If breathing is difficult, give oxygen. Call a physician if symptoms occur.
First-aid measures after skin contact	: Wash immediately with plenty of water. Call a physician if symptoms occur.
First-aid measures after eye contact	: Rinse immediately with plenty of water (for at least 15 minutes). Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician if symptoms occur.
First-aid measures after ingestion	: Rinse mouth thoroughly with water. Do NOT induce vomiting unless directed to do so by a physician. If a person vomits when lying on his back, place them in the recovery position. Call a physician if symptoms occur.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation	: Inhalation may cause irritation (cough, short breathing, difficulty in breathing).
Symptoms/effects after skin contact	: May cause skin irritation.
Symptoms/effects after eye contact	: May cause eye irritation.
Symptoms/effects after ingestion	: Ingestion may cause nausea, vomiting and diarrhea. May cause irritation to the digestive tract.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Use extinguishing media appropriate for surrounding fire. water spray, carbon dioxide (CO ₂), foam and powder. Use a water spray to cool packaging exposed to fire.
Unsuitable extinguishing media	: high volume water jet.

Fast Wax

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

5.2. Special hazards arising from the substance or mixture

- Fire hazard : Incomplete combustion may form toxic pyrolysis products.
Hazardous decomposition products in case of fire : Carbon dioxide (CO₂). carbon monoxide. Toxic fumes may be released.

5.3. Advice for firefighters

- Precautionary measures fire : Evacuate area.
Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
Other information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Keep people away from and upwind of spill/leak.

For non-emergency personnel

- Protective equipment : Wear personal protective equipment. Avoid contact with eyes, skin and clothing. Do not breathe gas/fumes/vapour/spray. Wear respiratory protection. Keep away unprotected persons.

- Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid contact with skin and eyes.

For emergency responders

- Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment. Do not flush into surface water or sewer system. Avoid subsoil penetration. If the product contaminates rivers and lakes or drains inform respective authorities.

6.3. Methods and material for containment and cleaning up

- Methods for cleaning up : Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

6.4. Reference to other sections

See Section 1 for emergency contact information.
See Section 8 for information on personal protective equipment.
See Section 13 for waste treatment information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Keep container tightly closed. Use appropriate personal protection equipment (PPE). Avoid contact with eyes, skin and clothing. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.
Hygiene measures : Handle in accordance with good industrial hygiene and safety procedures.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Take precautionary measures against static discharge.
Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed. Keep in an area equipped with solvent resistant flooring.
Incompatible materials : Store away from incompatible materials (see section 10).
Heat and ignition sources : The product is not flammable. Normal measures for preventive fire protection.
Information on mixed storage : Keep away from food, drink and animal feedingstuffs.

Fast Wax

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Storage area : Store away from heat/moisture.
Special rules on packaging : Keep only in original container.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

National occupational exposure and biological limit values

N-Butanol (71-36-3)	
United Kingdom - Occupational Exposure Limits	
Local name	Butan-1-ol
WEL STEL (OEL STEL)	154 mg/m ³
	50 ppm
Remark	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
Monoethylene Glycol (107-21-1)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Ethylene glycol
IOEL TWA	52 mg/m ³
	20 ppm
IOEL STEL	104 mg/m ³
	40 ppm
Remark	Skin
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
United Kingdom - Occupational Exposure Limits	
Local name	Ethane-1,2-diol
WEL TWA (OEL TWA)	10 mg/m ³ particulate
	52 mg/m ³ vapour
	20 ppm vapour
WEL STEL (OEL STEL)	104 mg/m ³ vapour
	40 ppm vapour
Remark	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
Aluminium Oxide (1344-28-1)	
United Kingdom - Occupational Exposure Limits	
Local name	Aluminium oxides
WEL TWA (OEL TWA)	10 mg/m ³ inhalable dust
	4 mg/m ³ respirable dust
WEL STEL (OEL STEL)*	30 mg/m ³

Fast Wax

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Aluminium Oxide (1344-28-1)

Regulatory reference EH40/2005 (Fourth edition, 2020). HSE

*STEL value is calculated based on the TWA limit

8.2. Exposure controls

Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station. Provide sufficient air exchange and/or exhaust.

Personal protection equipment

Personal protective equipment symbol(s):



Eye and face protection

Eye protection

Type	Field of application	Characteristics	Standard
Safety glasses, Safety goggles	Liquid, spray, Droplet	With side shields, Wear a face shield	EN 166

Skin protection

Skin and body protection:

Wear suitable protective clothing

Hand protection:

Protective gloves. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Protective gloves should be replaced at first signs of wear.

Hand protection

Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Disposable gloves	Butyl rubber, Neoprene or nitrile rubber gloves, PVC	6 (> 480 minutes)	≥0.5		EN ISO 374

Respiratory protection

Respiratory protection

Device	Filter type	Condition	Standard
	Type A - High-boiling (>65 °C) organic compounds	Vapour protection, Protection for Liquid particles	EN 14387

Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Blue.
Odour	: Bilberry.
Odour threshold	: Not available
Melting point	: Not available

Fast Wax

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Freezing point	: Not available
Boiling point	: Not available
Flammability	: Not available
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: Not available
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: 5.5 – 7.5
Viscosity, kinematic	: Not available
Solubility	: Not available
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not available
Vapour pressure at 50°C	: Not available
Density	: Not available
Relative density	: Not available
Relative vapour density at 20°C	: Not available
Particle characteristics	: Not applicable

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Does not decompose when used and stored as recommended.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Keep away from heat, sparks and flame. Take precautionary measures against static discharge.

10.5. Incompatible materials

Strong oxidizing agents. Strong acid or strong base.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics, (2-25%)	
LD50 oral rat	> 15000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 dermal rat	3400 mg/kg
LC50 Inhalation - Rat (Vapours)	13100 mg/l/4h

Fast Wax

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

N-Butanol (71-36-3)	
LD50 dermal rabbit	3430 mg/kg (Rabbit, male) (OECD Test Guideline 402)
LD50 dermal	0
2-methylisothiazol-3(2H)-one (2682-20-4)	
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
Monoethylene Glycol (107-21-1)	
LD50 oral rat	7712 mg/kg bodyweight Animal: rat
LD50 oral	7712 mg/kg bodyweight
LD50 dermal	10600 mg/kg bodyweight
LC50 Inhalation - Rat (Dust/Mist)	> 2500 mg/l
Skin corrosion/irritation	: Not classified pH: 5.5 – 7.5
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics, (2-25%)	
pH	5.5 – 6.5
N-Butanol (71-36-3)	
pH	7
2-methylisothiazol-3(2H)-one (2682-20-4)	
pH	2.58 Temp.: 25 °C Concentration: 50 g/L
Monoethylene Glycol (107-21-1)	
pH	7
Serious eye damage/irritation	: Not classified pH: 5.5 – 7.5
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics, (2-25%)	
pH	5.5 – 6.5
N-Butanol (71-36-3)	
pH	7
2-methylisothiazol-3(2H)-one (2682-20-4)	
pH	2.58 Temp.: 25 °C Concentration: 50 g/L
Monoethylene Glycol (107-21-1)	
pH	7
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
2-methylisothiazol-3(2H)-one (2682-20-4)	
NOAEL (animal/female, F0/P)	112 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: EPA OPPTS 870.3800 (Reproduction and Fertility Effects)
NOAEL (animal/female, F1)	56.6 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: EPA OPPTS 870.3800 (Reproduction and Fertility Effects)

Fast Wax

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Aluminium Oxide (1344-28-1)	
NOAEL (animal/male, F0/P)	1000 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
STOT-single exposure	: Not classified
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics, (2-25%)	
STOT-single exposure	May cause drowsiness or dizziness.
N-Butanol (71-36-3)	
STOT-single exposure	May cause respiratory irritation. May cause drowsiness or dizziness.
STOT-repeated exposure	: May cause damage to organs through prolonged or repeated exposure.
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics, (2-25%)	
NOAEL (dermal, rat/rabbit, 90 days)	≥ 495 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 411 (Subchronic Dermal Toxicity: 90-Day Study)
STOT-repeated exposure	Causes damage to organs (Central nervous system) through prolonged or repeated exposure (inhalation).
2-methylisothiazol-3(2H)-one (2682-20-4)	
LOAEL (oral, rat, 90 days)	71.2 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents), Guideline: other:
Monoethylene Glycol (107-21-1)	
STOT-repeated exposure	May cause damage to organs (kidneys) through prolonged or repeated exposure (inhalation).
Aluminium Oxide (1344-28-1)	
LOAEC (inhalation, rat, dust/mist/fume, 90 days)	0.015 mg/l air Animal: rat, Guideline: OECD Guideline 452 (Chronic Toxicity Studies)
Aspiration hazard	: Not classified
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics, (2-25%)	
Viscosity, kinematic	1.2 mm ² /s Temp.: '20°C' Parameter: 'kinematic viscosity (in mm ² /s)'
Hydrocarbon	Yes
N-Butanol (71-36-3)	
Viscosity, kinematic	3.641 mm ² /s
2-methylisothiazol-3(2H)-one (2682-20-4)	
Viscosity, kinematic	Not applicable

11.2. Information on other hazards

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Harmful to aquatic life with long lasting effects.

Fast Wax

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics, (2-25%)	
LC50 - Fish [1]	10 – 30 mg/l (Oncorhynchus mykiss (rainbow trout); 96 h)
EC50 - Crustacea [1]	10 – 22 mg/l (Daphnia magna (Water flea); 48 h)
EC50 72h - Algae [1]	0.94 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 72h - Algae [2]	0.53 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 96h - Algae [1]	1.2 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 96h - Algae [2]	0.58 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
N-Butanol (71-36-3)	
LC50 - Fish [1]	1.376 mg/l (Pimephales promelas; 96 h) (static test; OECD Test Guideline 203)
EC50 - Crustacea [1]	1.328 mg/l (Daphnia magna (Water flea); 48 h) (static test; OECD Test Guideline 202)
EC50 - Crustacea [2]	225 mg/l (Pseudokirchneriella subcapitata (green algae); 96 h) (static test; End point: Growth rate; OECD Test Guideline 201)
NOEC chronic crustacea	4.1 mg/l (Daphnia magna (Water flea); 21 d) (semi-static test; End point: Reproduction; OECD Test Guideline 211)
NOEC chronic algae	2476 mg/l (Pseudomonas putida; 17 h) (static test; End point: Growth rate; DIN 38412)
2-methylisothiazol-3(2H)-one (2682-20-4)	
LC50 - Fish [1]	4.77 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
LC50 - Fish [2]	2.15 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 - Crustacea [1]	1.6 mg/l Test organisms (species): Daphnia magna
EC50 - Crustacea [2]	2.9 mg/l Test organisms (species): Daphnia magna
Monoethylene Glycol (107-21-1)	
LC50 - Fish [1]	> 72860 mg/l Test organisms (species): Pimephales promelas
EC50 - Crustacea [1]	> 100 mg/l Test organisms (species): Daphnia magna
EC50 - Other aquatic organisms [1]	> 100 mg/l waterflea
EC50 - Other aquatic organisms [2]	6500 mg/l
NOEC (chronic)	≥ 1000 mg/l Test organisms (species): Americamysis bahia (previous name: Mysidopsis bahia) Duration: '23 d'
Aluminium Oxide (1344-28-1)	
EC50 72h - Algae [1]	1.05 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)
EC50 72h - Algae [2]	0.2 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)
12.2. Persistence and degradability	
Fast Wax	
Persistence and degradability	Not rapidly degradable

Fast Wax

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics, (2-25%)	
Persistence and degradability	Not rapidly degradable
N-Butanol (71-36-3)	
Persistence and degradability	Not rapidly degradable
2-methylisothiazol-3(2H)-one (2682-20-4)	
Persistence and degradability	Not rapidly degradable
Monoethylene Glycol (107-21-1)	
Persistence and degradability	Not rapidly degradable
Aluminium Oxide (1344-28-1)	
Persistence and degradability	Not rapidly degradable

12.3. Bioaccumulative potential

Monoethylene Glycol (107-21-1)	
Partition coefficient n-octanol/water (Log Pow)	-1.36

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions. Disposal together with normal waste is not allowed.
Product/Packaging disposal recommendations	: Special disposal required according to local regulations. Do not let product enter drains. Contact waste disposal services. This product shall be disposed of or recovered in compliance with Directive 2008/98/EC on waste as lastly amended.
HP Code	: HP5 - "Specific Target Organ Toxicity (STOT)/Aspiration Toxicity:" waste which can cause specific target organ toxicity either from a single or repeated exposure, or which cause acute toxic effects following aspiration. HP14 - "Ecotoxic:" waste which presents or may present immediate or delayed risks for one or more sectors of the environment

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID number				
Not regulated for transport				

Fast Wax

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ADR	IMDG	IATA	ADN	RID
14.2. UN proper shipping name				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.3. Transport hazard class(es)				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.4. Packing group				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.5. Environmental hazards				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
No supplementary information available				

14.6. Special precautions for user

Overland transport

Not regulated

Transport by sea

Not regulated

Air transport

Not regulated

Inland waterway transport

Not regulated

Rail transport

Not regulated

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU-Regulations

REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (2024/590)

Not listed on the Ozone Depletion list (Regulation EU 2024/590)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 2024/590 on substances that deplete the ozone layer)

Fast Wax

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Council Regulation (EC) for the control of dual-use items

Contains substance subject to the COUNCIL REGULATION (EC) for the control of dual-use items: Aluminium oxide (1344-28-1).

Explosives Precursors Regulation (EU 2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (EC 273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.2. Chemical safety assessment

No additional information available

SECTION 16: Other information

Abbreviations and acronyms:

ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant

Fast Wax

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Abbreviations and acronyms:

ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstracts Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disruptor

Full text of H- and EUH-statements:

Acute Tox. 2 (Inhalation)	Acute toxicity (inhal.), Category 2
Acute Tox. 3 (Dermal)	Acute toxicity (dermal), Category 3
Acute Tox. 3 (Oral)	Acute toxicity (oral), Category 3
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Flam. Liq. 3	Flammable liquids, Category 3
Skin Corr. 1B	Skin corrosion/irritation, Category 1, Sub-Category 1B
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1A	Skin sensitisation, category 1A
STOT RE 1	Specific target organ toxicity – Repeated exposure, Category 1
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis
H226	Flammable liquid and vapour.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H330	Fatal if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.

Fast Wax

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements:	
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.
EUH071	Corrosive to the respiratory tract.

The classification complies with : ATP 12

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.