

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form	: Substance (UVCB)
Substance name	: Glue & Tar Remover
Chemical name	: Hydrocarbons, C9, Aromatics
EC-No.	: 918-668-5
CAS-No.	: 64742-95-6
REACH registration No.	: 01-2119455851-35
Product code	: VC212

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Main use category	: Industrial use, Professional use
Use of the substance/mixture	: Cleaning/washing agents and additives

1.3. Details of the supplier of the safety data sheet

Supplier

Valet-Chem Ltd
Summit Close
NG17 8GJ Kirkby In Ashfield Nottingham, Nottinghamshire
United Kingdom
T T +44 (0) 844 414 0987
info@valetchem.co.uk

Supplier information

Leading Solvents Ireland Ltd
The Courtyard, Manor House
3 Church Road
Malahide, Co. Dublin
Ireland
T +353 1 845 7660

1.4. Emergency telephone number

Emergency number : +44 (0) 844 414 0987 (Office hours only)

Country/Area	Organisation	Emergency number
Ireland	National Poisons Information Centre. Beaumont Hospital. PO Box 1297. Beaumont Road 9 Dublin.	+353 1 809 2566 (Healthcare professionals-24/7) +353 1 809 2166 (public, 8am - 10pm, 7/7)
United Kingdom	NHS 111/NHS 24/NHS Direct.	111 0845 4647 or call a doctor

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids, Category 3	H226
Specific target organ toxicity – Single exposure, Category 3, Narcosis	H336
Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation	H335
Aspiration hazard, Category 1	H304
Hazardous to the aquatic environment – Chronic Hazard, Category 2	H411

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

See section 11 for toxicological information. See section 9/10 for physicochemical information. See section 12 for environmental information.

Glue & Tar Remover

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



Signal word (CLP)

: Danger

Contains

: Hydrocarbons, C9, aromatics

Hazard statements (CLP)

: H226 - Flammable liquid and vapour.
H304 - May be fatal if swallowed and enters airways.
H335 - May cause respiratory irritation.
H336 - May cause drowsiness or dizziness.
H411 - Toxic to aquatic life with long lasting effects.

Precautionary statements (CLP)

: P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P273 - Avoid release to the environment.
P240 - Ground and bond container and receiving equipment.
P241 - Use explosion-proof electrical, lighting, ventilating equipment.
P242 - Use non-sparking tools.
P243 - Take action to prevent static discharges.
P261 - Avoid breathing mist, spray, vapours.
P271 - Use only outdoors or in a well-ventilated area.
P280 - Wear protective clothing, eye protection, face protection, protective gloves.
P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER, a doctor.
P331 - Do NOT induce vomiting.
P370+P378 - In case of fire: Use dry sand, alcohol resistant foam, dry extinguishing powder to extinguish.
P391 - Collect spillage.
P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P312 - Call a POISON CENTER, doctor if you feel unwell.
P403+P235 - Store in a well-ventilated place. Keep cool.
P405 - Store locked up.
P501 - Dispose of contents and container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

EUH-statements

: EUH066 - Repeated exposure may cause skin dryness or cracking.

2.3. Other hazards

Other hazards which do not result in classification

: Vapours may form explosive mixtures with air. Static-accumulating. Even with proper grounding and bonding, this material can still accumulate an electrostatic charge. If sufficient charge is allowed to accumulate, electrostatic discharge and ignition of flammable air-vapour mixtures can occur.

Contains no PBT and/or vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

SECTION 3: Composition/information on ingredients

3.1. Substances

Substance type

: UVCB

Name

: Glue & Tar Remover

CAS-No.

: 64742-95-6

EC-No.

: 918-668-5

Glue & Tar Remover

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Glue & Tar Remover	CAS-No.: 64742-95-6 EC-No.: 918-668-5 REACH-no: 01-2119455851-35	100	See Section 2.1
Benzene	CAS-No.: 71-43-2 EC-No.: 200-753-7	< 0.1	Not classified
cumene	CAS-No.: 98-82-8 EC-No.: 202-704-5 EC Index-No.: 601-024-00-X	< 0.1	Flam. Liq. 3, H226 Carc. 1B, H350 Asp. Tox. 1, H304 STOT SE 3, H335 Aquatic Chronic 2, H411

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Take off all contaminated clothing immediately . Wash contaminated clothing before reuse.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. If breathing is irregular or stopped, administer artificial respiration. If respiratory irritation, dizziness, nausea, or unconsciousness occurs, seek immediate medical assistance.
First-aid measures after skin contact	: Rinse skin with water/shower. Take off immediately all contaminated clothing. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Rinse mouth out with water. Never give anything by mouth to an unconscious person. Do NOT induce vomiting unless directed to do so by a physician. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation	: Inhalation may cause irritation (cough, short breathing, difficulty in breathing). Breathing of high vapour concentrations may cause central nervous system (CNS) depression resulting in dizziness, lightheadedness, headache, nausea and loss of coordination.
Symptoms/effects after skin contact	: irritation (itching, redness, blistering). Repeated exposure may cause skin dryness or cracking.
Symptoms/effects after eye contact	: redness, itching, tears. Causes eye irritation. stinging.
Symptoms/effects after ingestion	: May cause irritation to the digestive tract.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. Risk of aspiration pneumonia.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: high volume water jet.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: The vapour may be invisible, heavier than air and spread along ground. Vapours may form explosive mixture with air. Flash back possible over considerable distance. Heating will cause a rise in pressure with a risk of bursting.
-------------	--

Glue & Tar Remover

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Hazardous decomposition products in case of fire : A complex mixture of airborne solids, liquids and gases including carbon monoxide, carbon dioxide, sulphur oxides and unidentified organic compounds will be evolved when this material undergoes combustion or thermal or oxidative degradation. . Flammable vapours may be present even at temperatures below the flash point. . Vapours are heavier than air and may travel considerable distance to an ignition source and flash back to source of vapours. Will float and can be reignited on water surface.

5.3. Advice for firefighters

Precautionary measures fire : Evacuate area.
Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
Other information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Protective equipment : Use personal protective equipment as required. Keep away unprotected persons. Do not breathe gas, fumes, vapour or spray.
Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid contact with skin and eyes.

For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment. Do not flush into surface water or sewer system. Avoid subsoil penetration. If the product contaminates rivers and lakes or drains inform respective authorities.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

6.4. Reference to other sections

See Section 1 for emergency contact information.
See Section 8 for information on personal protective equipment.
See Section 13 for waste treatment information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Avoid contact with skin and eyes. Do not breathe gas, fumes, vapour or spray.
Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ground/bond container and receiving equipment. Take precautionary measures against static discharge.

Glue & Tar Remover

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

- Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed. Keep in an area equipped with solvent resistant flooring.
- Incompatible materials : Store away from incompatible materials (see section 10).
- Heat and ignition sources : The vapour may be invisible, heavier than air and spread along ground. Can form explosive mixture with air.
- Information on mixed storage : Keep away from food, drink and animal feedingstuffs.
- Storage area : Store away from heat.
- Packaging materials : Avoid prolonged contact with natural, butyl or nitrile rubbers.

Germany

Storage class (LGK, TRGS 510)

Joint storage table

: LGK 3 - Flammable liquids

LGK 1	LGK 2A	LGK 2B	LGK 3	LGK 4.1A
LGK 4.1B	LGK 4.2	LGK 4.3	LGK 5.1A	LGK 5.1B
LGK 5.1C	LGK 5.2	LGK 6.1A	LGK 6.1B	LGK 6.1C
LGK 6.1D	LGK 6.2	LGK 7	LGK 8A	LGK 8B
LGK 10	LGK 11	LGK 12	LGK 13	LGK 10-13

Joint storage not permitted for

: LGK 1, LGK 2A, LGK 4.1A, LGK 4.1B, LGK 4.2, LGK 4.3, LGK 5.1A, LGK 5.1C, LGK 5.2, LGK 6.1B, LGK 6.2, LGK 7

Joint storage with restrictions permitted for

: LGK 5.1B, LGK 6.1D, LGK 11, LGK 10-13

Joint storage permitted for

: LGK 2B, LGK 3, LGK 6.1A, LGK 6.1C, LGK 8A, LGK 8B, LGK 10, LGK 12, LGK 13

Switzerland

Storage class (LK)

: LK 3 - Flammable liquids

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

DNEL and PNEC

Glue & Tar Remover (64742-95-6)	
DNEL/DMEL (Workers)	
Long-term - local effects, dermal	25 mg/kg bw/day
Long-term - systemic effects, inhalation	150 mg/m ³
DNEL/DMEL (General population)	
Long-term - systemic effects, inhalation	32 mg/m ³
Long-term - systemic effects, dermal	11 mg/kg bw/day

8.2. Exposure controls

Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

Personal protection equipment

Personal protective equipment symbol(s):



Glue & Tar Remover

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Eye and face protection

Eye protection:

Safety glasses

Eye protection			
Type	Field of application	Characteristics	Standard
Safety glasses, Safety goggles	Liquid, Droplet, spray	With side shields	EN 166

Skin protection

Skin and body protection:

Wear suitable protective clothing

Hand protection:

Protective gloves. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Protective gloves should be replaced at first signs of wear.

Hand protection					
Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Disposable gloves	Nitrile rubber (NBR), Butyl rubber, Polyvinylchloride (PVC)	6 (> 480 minutes)	> 0.35		EN ISO 374

Respiratory protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

Respiratory protection			
Device	Filter type	Condition	Standard
	Type A - High-boiling (>65 °C) organic compounds	Vapour protection, Protection for Liquid particles	EN 14387

Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Colourless.
Odour	: aromatic.
Odour threshold	: Not available
Melting point	: Not applicable
Freezing point	: Not available
Boiling point	: 150 – 185 °C
Flammability	: Not applicable
Explosive properties	: formation of explosive air/vapour mixtures are possible.
Oxidising properties	: Not oxidising.
Lower explosion limit	: 0.6 Vol-%
Upper explosion limit	: 7 Vol-%
Flash point	: 38 – 50 °C IP 170
Auto-ignition temperature	: 507 °C
Decomposition temperature	: Not available
pH	: 7
Viscosity, kinematic	: 0.9 mm ² /s (25 °C) (ASTM D445)

Glue & Tar Remover

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Solubility	: Insoluble.
Partition coefficient n-octanol/water (Log Kow)	: Not available
Partition coefficient n-octanol/water (Log Pow)	: 3.7 – 4.5
Vapour pressure	: 210 – 1300 Pa (20 °C)
Vapour pressure at 50°C	: Not available
Density	: 876 kg/m ³ (15 °C) (ASTM D4052)
Relative density	: 0.87 – 0.88 (20 °C) (ASTM D4052)
Relative vapour density at 20°C	: 4.3
Particle characteristics	: Not applicable

9.2. Other information

Other safety characteristics

Relative evaporation rate (butylacetate=1)	: < 1 (ASTM D3539)
Specific conductivity	: < 100 pS/m The conductivity of this material makes it a static accumulator. A liquid is typically considered nonconductive if its conductivity is below 100 pS/m and is considered semi-conductive if its conductivity is below 10,000 pS/m. Whether a liquid is nonconductive or semi-conductive, the precautions are the same. A number of factors, for example liquid temperature, presence of contaminants, and anti-static additives can greatly influence the conductivity of a liquid.

SECTION 10: Stability and reactivity

10.1. Reactivity

Highly flammable liquid and vapour.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition. Do not pressurise, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous decomposition products

A complex mixture of airborne solids, liquids and gases including carbon monoxide, carbon dioxide, sulphur oxides and unidentified organic compounds will be evolved when this material undergoes combustion or thermal or oxidative degradation.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

Glue & Tar Remover (64742-95-6)	
LD50 oral rat	3592 mg/kg (Rat) (OECD Test Guideline 401)
LD50 dermal rabbit	> 3160 mg/kg (OECD Test Guideline 402)

Glue & Tar Remover

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Benzene (71-43-2)	
LD50 oral rat	> 2000 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LC50 Inhalation - Rat	43.767 mg/l air Animal: rat, Animal sex: female, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity), 95% CL: 41690 - 45939

Skin corrosion/irritation	: Not classified pH: 7
Serious eye damage/irritation	: Not classified pH: 7
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: May cause drowsiness or dizziness. May cause respiratory irritation.

cumene (98-82-8)	
STOT-single exposure	May cause respiratory irritation.
STOT-repeated exposure	: Not classified

Benzene (71-43-2)	
NOAEL (oral, rat, 90 days)	100 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)

Aspiration hazard	: May be fatal if swallowed and enters airways.
-------------------	---

Glue & Tar Remover (64742-95-6)	
Viscosity, kinematic	0.9 mm ² /s (25 °C) (ASTM D445)

Benzene (71-43-2)	
Viscosity, kinematic	0.689 mm ² /s

11.2. Information on other hazards

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Toxic to aquatic life with long lasting effects.

Glue & Tar Remover (64742-95-6)	
LC50 - Fish [1]	9.2 mg/l (Oncorhynchus mykiss (rainbow trout); 96h) (Toxicity to fish; Petrotox computer model (v3.04))
EC50 - Crustacea [1]	3.2 mg/l (Daphnia magna (Water flea); 48 h) (Toxicity to daphnia; OECD Test Guideline 202)
EC50 72h - Algae [1]	2.6 – 2.9 mg/l (Pseudokirchneriella subcapitata (microalgae); 72 h) (Toxicity to algae; Petrotox computer model (v3.04))
NOEC chronic fish	1.23 mg/l (Oncorhynchus mykiss (rainbow trout); 28 d) (Petrotox computer model (v3.04))
NOEC chronic crustacea	2.14 mg/l (Water flea); 21 d) (Petrotox computer model (v3.04))

Glue & Tar Remover

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Benzene (71-43-2)	
LC50 - Fish [1]	5.3 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 72h - Algae [1]	32 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)
EC50 72h - Algae [2]	100 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)
NOEC chronic fish	0.8 mg/l Test organisms (species): Pimephales promelas Duration: '32 d'

12.2. Persistence and degradability

Glue & Tar Remover (64742-95-6)	
Persistence and degradability	Not rapidly degradable
cumene (98-82-8)	
Persistence and degradability	Not rapidly degradable
Benzene (71-43-2)	
Persistence and degradability	Not rapidly degradable

12.3. Bioaccumulative potential

Glue & Tar Remover (64742-95-6)	
Partition coefficient n-octanol/water (Log Pow)	3.7 – 4.5

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions. Disposal together with normal waste is not allowed.
Product/Packaging disposal recommendations	: Special disposal required according to local regulations. Do not let product enter drains. Contact waste disposal services. This product shall be disposed of or recovered in compliance with Directive 2008/98/EC on waste as lastly amended.
Additional information	: Flammable vapours may accumulate in the container.

Glue & Tar Remover

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

HP Code

- : HP3 - "Flammable:"
 - flammable liquid waste: liquid waste having a flash point below 60 °C or waste gas oil, diesel and light heating oils having a flash point > 55 °C and ≤ 75 °C;
 - flammable pyrophoric liquid and solid waste: solid or liquid waste which, even in small quantities, is liable to ignite within five minutes after coming into contact with air;
 - flammable solid waste: solid waste which is readily combustible or may cause or contribute to fire through friction;
 - flammable gaseous waste: gaseous waste which is flammable in air at 20 °C and a standard pressure of 101.3 kPa;
 - water reactive waste: waste which, in contact with water, emits flammable gases in dangerous quantities;
 - other flammable waste: flammable aerosols, flammable self-heating waste, flammable organic peroxides and flammable self-reactive waste.
- HP5 - "Specific Target Organ Toxicity (STOT)/Aspiration Toxicity:" waste which can cause specific target organ toxicity either from a single or repeated exposure, or which cause acute toxic effects following aspiration.
- HP14 - "Ecotoxic:" waste which presents or may present immediate or delayed risks for one or more sectors of the environment

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID number				
UN 1268	UN 1268	UN 1268	UN 1268	UN 1268
14.2. UN proper shipping name				
PETROLEUM DISTILLATES, N.O.S. (Hydrocarbons, C9, aromatics)	PETROLEUM DISTILLATES, N.O.S. (Hydrocarbons, C9, aromatics)	Petroleum distillates, n.o.s. (Hydrocarbons, C9, aromatics)	PETROLEUM DISTILLATES, N.O.S. (Hydrocarbons, C9, aromatics)	PETROLEUM DISTILLATES, N.O.S. (Hydrocarbons, C9, aromatics)
Transport document description				
UN 1268 PETROLEUM DISTILLATES, N.O.S. (Hydrocarbons, C9, aromatics), 3, III, (D/E), ENVIRONMENTALLY HAZARDOUS	UN 1268 PETROLEUM DISTILLATES, N.O.S. (Hydrocarbons, C9, aromatics), 3, III, MARINE POLLUTANT/ENVIRONMENTALLY HAZARDOUS	UN 1268 Petroleum distillates, n.o.s. (Hydrocarbons, C9, aromatics), 3, III, ENVIRONMENTALLY HAZARDOUS	UN 1268 PETROLEUM DISTILLATES, N.O.S. (Hydrocarbons, C9, aromatics), 3, III, ENVIRONMENTALLY HAZARDOUS	UN 1268 PETROLEUM DISTILLATES, N.O.S. (Hydrocarbons, C9, aromatics), 3, III, ENVIRONMENTALLY HAZARDOUS
14.3. Transport hazard class(es)				
3	3	3	3	3
14.4. Packing group				
III	III	III	III	III
14.5. Environmental hazards				
Dangerous for the environment: Yes	Dangerous for the environment: Yes Marine pollutant: Yes EmS-No. (Fire): F-E EmS-No. (Spillage): S-E	Dangerous for the environment: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes
No supplementary information available				



Glue & Tar Remover

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

14.6. Special precautions for user

Overland transport

Classification code (ADR)	: F1
Special provisions (ADR)	: 664
Limited quantities (ADR)	: 5I
Excepted quantities (ADR)	: E1
Packing instructions (ADR)	: P001, IBC03, LP01, R001
Mixed packing provisions (ADR)	: MP19
Portable tank and bulk container instructions (ADR)	: T4
Portable tank and bulk container special provisions (ADR)	: TP1, TP29
Tank code (ADR)	: LGBF
Vehicle for tank carriage	: FL
Transport category (ADR)	: 3
Special provisions for carriage - Packages (ADR)	: V12
Special provisions for carriage - Operation (ADR)	: S2
Hazard identification number (Kemler No.)	: 30
Orange plates	: 
	: 
Tunnel restriction code (ADR)	: D/E
EAC code	: 3Y

Transport by sea

Special provisions (IMDG)	: 223, 955
Limited quantities (IMDG)	: 5 L
Excepted quantities (IMDG)	: E1
Packing instructions (IMDG)	: P001, LP01
IBC packing instructions (IMDG)	: IBC03
Tank instructions (IMDG)	: T4
Tank special provisions (IMDG)	: TP1, TP29
Stowage category (IMDG)	: A
Properties and observations (IMDG)	: Immiscible with water.

Air transport

PCA Excepted quantities (IATA)	: E1
PCA Limited quantities (IATA)	: Y344
PCA limited quantity max net quantity (IATA)	: 10L
PCA packing instructions (IATA)	: 355
PCA max net quantity (IATA)	: 60L
CAO packing instructions (IATA)	: 366
CAO max net quantity (IATA)	: 220L
Special provisions (IATA)	: A3
ERG code (IATA)	: 3L

Inland waterway transport

Classification code (ADN)	: F1
Limited quantities (ADN)	: 5 L
Excepted quantities (ADN)	: E1
Carriage permitted (ADN)	: T
Equipment required (ADN)	: PP, EX, A
Ventilation (ADN)	: VE01
Number of blue cones/lights (ADN)	: 0

Rail transport

Classification code (RID)	: F1
Limited quantities (RID)	: 5L
Excepted quantities (RID)	: E1
Packing instructions (RID)	: P001, IBC03, LP01, R001
Mixed packing provisions (RID)	: MP19

Glue & Tar Remover

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Portable tank and bulk container instructions (RID)	: T4
Portable tank and bulk container special provisions (RID)	: TP1, TP29
Tank codes for RID tanks (RID)	: LGBF
Transport category (RID)	: 3
Special provisions for carriage – Packages (RID)	: W12
Colis express (express parcels) (RID)	: CE4
Hazard identification number (RID)	: 30

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU-Regulations

REACH Annex XVII (Restriction List)

Not listed on REACH Annex XVII

REACH Annex XIV (Authorisation List)

Not listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals): Benzene (71-43-2)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (2024/590)

Not listed on the Ozone Depletion list (Regulation EU 2024/590)

Council Regulation (EC) for the control of dual-use items

Contains no substance subject to the COUNCIL REGULATION (EC) for the control of dual-use items

Explosives Precursors Regulation (EU 2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (EC 273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

National regulations

Austria

Ordinance on Flammable Liquids (VbF)	: Hazard category 3: Flammable (flash point 23 - 60 °C. Excluding gas oils and petroleum).
Toxic Substances Ordinance 2000	: Is not subject to the Toxic Substances Ordinance 2000.

Denmark

Class for fire hazard	: Class II-1
Store unit	: 5 liter
Classification remarks	: R10 <H226;H304;H335;H336;H411>; Emergency management guidelines for the storage of flammable liquids must be followed

Glue & Tar Remover

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Danish National Regulations

- : Young people below the age of 18 years are not allowed to use the product
Pregnant/breastfeeding women working with the product must not be in direct contact with it.
If an employee is pregnant or breastfeeding and the person in question uses or is exposed to this product at work, the employer must always carry out a risk assessment of the work. The assessment must both deal with the dangerousness of the impact and its strength and duration. The employer's decision that a pregnant or lactating woman can perform a specific work task must therefore be made in the context of her specific working conditions. See also WEA-Guideline A.1.8-7 on the working environment of pregnant and breastfeeding workers. Listed or contains substance(s) on the Denmark - Indicative list of organic solvents present in Annex 3.4.1 of the WEA Guidance C.0.1-1: Isopropylbenzene (1994) (98-82-8), Benzene (1996) (71-43-2)

France

Occupational diseases	
Code	Description
RG 4	Hematopathies caused by benzene and all products containing it
RG 4 BIS	Gastrointestinal disorders caused by benzene, toluene, xylenes and all products containing them
RG 84	Conditions caused by liquid organic solvents for professional use: saturated or unsaturated aliphatic or cyclic liquid hydrocarbons and mixtures thereof; liquid halogenated hydrocarbons; nitrated derivatives of aliphatic hydrocarbons; alcohols; glycols, glycol ethers; ketones; aldehydes; aliphatic and cyclic ethers, including tetrahydrofuran; esters; dimethylformamide and dimethylacetamine; acetonitrile and propionitrile; pyridine; dimethylsulfone and dimethylsulfoxide

Germany

Employment restrictions

- : Observe restrictions according Act on the Protection of Working Mothers (MuSchG).
Observe restrictions according Act on the Protection of Young People in Employment (JArbSchG).

Water hazard class (WGK)

- : WGK 3, Highly hazardous to water (Classification according to AwSV; ID No. 9162).

Major Accidents Ordinance (12. BImSchV)

- : Is listed in the Major Accidents Ordinance (12. BImSchV)

Major Accidents Ordinance (12. BImSchV)				
Number	Code	Title	Lower-tier	Upper-tier
1.2.5.1	P5a	Flammable liquids. Flammable liquids of category 1; flammable liquids of category 2 or 3 maintained at a temperature above their boiling point; other liquids with a flash point of ≤ 60 °C maintained at a temperature above their boiling point	10,000 kg	50,000 kg
1.2.5.2	P5b	Flammable liquids. Flammable liquids of category 2 or 3, where special processing conditions such as high pressure or high temperature can lead to the risk of accidents; other liquids with a flash point of ≤ 60 °C, where special processing conditions such as high pressure or high temperature can lead to the risk of accidents	50,000 kg	200,000 kg
1.2.5.3	P5c	Flammable liquids of categories 2 or 3, not covered under P5a and P5b	5,000,000 kg	50,000,000 kg
1.3.2	E2	Hazardous to the aquatic environment, Chronic 2	200,000 kg	500,000 kg

Netherlands

ABM category

- : A(2) - toxic for aquatic organisms, may have longterm hazardous effects in aquatic environment

SZW-lijst van kankerverwekkende stoffen

- : The substance is not listed

SZW-lijst van mutagene stoffen

- : The substance is not listed

SZW-lijst van reprotoxische stoffen – Borstvoeding

- : The substance is not listed

SZW-lijst van reprotoxische stoffen –

- : The substance is not listed

Vruchtbaarheid

SZW-lijst van reprotoxische stoffen – Ontwikkeling

- : The substance is not listed

Glue & Tar Remover

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Poland

Polish National Regulations

: Act of 25 February 2011 on chemical substances and their mixtures (J. o L. No. 63, item 322 as amended; consolidated text J. o L. 2019, item 1225).
Act of 14 December 2012 on waste (J. o L. 2013, item 322 as amended; consolidated text J. o L. 2020, item 797).
The announcement of Marshal of the Sejm of the Republic of Poland dated 19 October 2016 concerning the consolidated text announcement of the decree on the management of packaging and packaging waste (J. o L. 2016, item 1863 as amended).
Decree of the Minister of Environment of 14 December 2014 on the catalogue of waste (J. o L. 2014, item 1923).
Act of 19 August 2011 on the Carriage of Dangerous Goods (J. o L. 2011 No. 227, item 1367 as amended; consolidated text J. o L. 2020, item 154).
Regulation of the Minister of Family, Labour and Social Policy of 12 June 2018 on the highest permissible concentration and intensity of noxious agents for health at work environment (J. o L. item 1286 as amended).
The announcement of Minister of Health dated 9 September 2016 concerning the consolidated text announcement of the decree of the Minister of Health of 30 December 2004 on health and safety at work related to exposure to chemical agents at work (J. o L. of 16 September 2016, item 1488)
Regulation of the Minister of Health of 2 February 2011 on tests and measurements of the noxious agents for health at work environment (J. o L. No. 33, item 166 as amended).
Regulation of the Minister of Environment of 9 December 2003 on particularly hazardous substances to the environment (J. o L. No. 217, item 2141).
ADR Agreement: Government Statement of 13 March 2023 on the entry into force of amendments to Annexes A and B to the Agreement concerning the International Carriage of Dangerous Goods by Road (ADR), signed in Geneva on 30 September 1957 (J. o. L. 2023, item 891)
Regulation of the Minister of Health of 25 August 2015 on the method of marking places, pipelines, and containers and tanks used for storing or containing hazardous substances or hazardous mixtures (J.o.L. 2015, item 1368 as amended)

Spain

Royal Decree 665/1997

: Is not subject to the Royal Decree 665/1997

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Indication of changes		
Section	Changed item	Comments
1.3	Additional information	Added Suppliers EU Address
1.4	Additional information	Added NHS 111 & EU Poison Centre

Abbreviations and acronyms:

ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)

Glue & Tar Remover

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Abbreviations and acronyms:	
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstracts Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disruptor

Full text of H- and EUH-statements:	
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Asp. Tox. 1	Aspiration hazard, Category 1
Carc. 1B	Carcinogenicity, Category 1B
Flam. Liq. 3	Flammable liquids, Category 3
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.

Glue & Tar Remover

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements:	
H350	May cause cancer.
H411	Toxic to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.