

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Substance  
 Substance name : N-Butyl Acetate  
 Chemical name : n-butyl acetate  
 EC Index-No. : 607-025-00-1  
 EC-No. : 204-658-1  
 CAS-No. : 123-86-4  
 REACH registration No. : 01-2119485493-29  
 Product code : BA  
 Formula : C6H12O2

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### Relevant identified uses

Main use category : Industrial use, Professional use  
 Use of the substance/mixture : Uses in Coatings  
 Adhesives  
 Cleaning/washing agents and additives  
 Cosmetics  
 Pharmaceuticals  
 Lubricants and additives  
 Laboratory chemicals  
 Textile industry  
 Aerosols

#### 1.3. Details of the supplier of the safety data sheet

##### Supplier

Valet-Chem Ltd  
 Summit Close  
 NG17 8GJ Kirkby In Ashfield Nottingham, Nottinghamshire  
 United Kingdom  
 T T +44 (0) 844 414 0987  
[info@valetchem.co.uk](mailto:info@valetchem.co.uk)

##### Supplier information

Leading Solvents Ireland Ltd  
 The Courtyard, Manor House  
 3 Church Road  
 Malahide, Co.Dubin  
 Ireland  
 T +353 1 845 7660

#### 1.4. Emergency telephone number

Emergency number : +44 (0) 844 414 0987 (Office hours only)

Country/Area	Organisation	Emergency number
Ireland	National Poisons Information Centre. Beaumont Hospital. PO Box 1297. Beaumont Road 9 Dublin.	+353 1 809 2566 (Healthcare professionals-24/7) +353 1 809 2166 (public, 8am - 10pm, 7/7)
United Kingdom	NHS 111/NHS 24/NHS Direct.	111 0845 4647 or call a doctor

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids, Category 3 H226  
 Specific target organ toxicity – Single exposure, Category 3, H336  
 Narcosis

Full text of H- and EUH-statements: see section 16

# N-Butyl Acetate

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878


### Adverse physicochemical, human health and environmental effects

See section 11 for toxicological information. See section 9/10 for physicochemical information. See section 12 for environmental information.

## 2.2. Label elements

### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



Signal word (CLP)

: Warning

Hazard statements (CLP)

: H226 - Flammable liquid and vapour.  
H336 - May cause drowsiness or dizziness.

Precautionary statements (CLP)

: P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P233 - Keep container tightly closed.  
P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.  
P280 - Wear protective clothing, eye protection, face protection.  
P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.  
P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P312 - Call a POISON CENTER, doctor if you feel unwell.

EUH-statements

: EUH066 - Repeated exposure may cause skin dryness or cracking.

## 2.3. Other hazards

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII

This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

The substance is not included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Substance type : Mono-constituent

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
N-Butyl Acetate	CAS-No.: 123-86-4 EC-No.: 204-658-1 EC Index-No.: 607-025-00-1 REACH-no: 01-2119485493-29	100	Flam. Liq. 3, H226 STOT SE 3, H336 EUH066

Full text of H- and EUH-statements: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general : Take off all contaminated clothing immediately . Wash contaminated clothing before reuse.

# N-Butyl Acetate

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. If breathing is irregular or stopped, administer artificial respiration. If respiratory irritation, dizziness, nausea, or unconsciousness occurs, seek immediate medical assistance.
First-aid measures after skin contact	: Rinse skin with water/shower. Take off immediately all contaminated clothing. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Rinse mouth out with water. Never give anything by mouth to an unconscious person. Do NOT induce vomiting unless directed to do so by a physician. Call a physician immediately.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation	: Inhalation may cause irritation (cough, short breathing, difficulty in breathing).
Symptoms/effects after skin contact	: irritation (itching, redness, blistering). Repeated exposure may cause skin dryness or cracking.
Symptoms/effects after eye contact	: redness, itching, tears. Causes eye irritation. stinging.
Symptoms/effects after ingestion	: May cause irritation to the digestive tract.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: high volume water jet.

### 5.2. Special hazards arising from the substance or mixture

Fire hazard	: Extremely flammable liquid and vapour. The vapour may be invisible, heavier than air and spread along ground. Vapours may form explosive mixture with air. Flash back possible over considerable distance. Heating will cause a rise in pressure with a risk of bursting.
Hazardous decomposition products in case of fire	: Toxic fumes may be released. Carbon oxides (CO, CO <sub>2</sub> ).

### 5.3. Advice for firefighters

Precautionary measures fire	: Evacuate area.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
Other information	: Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Stop leak if safe to do so.
------------------	---

#### For non-emergency personnel

Protective equipment	: Use personal protective equipment as required. Keep away unprotected persons. Do not breathe gas, fumes, vapour or spray.
Emergency procedures	: Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid contact with skin and eyes.

#### For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
----------------------	---

# N-Butyl Acetate

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 6.2. Environmental precautions

Avoid release to the environment. Do not flush into surface water or sewer system. Avoid subsoil penetration. If the product contaminates rivers and lakes or drains inform respective authorities.

### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

### 6.4. Reference to other sections

See Section 1 for emergency contact information.  
See Section 8 for information on personal protective equipment.  
See Section 13 for waste treatment information.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Avoid contact with skin and eyes. Do not breathe gas, fumes, vapour or spray.

Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ground/bond container and receiving equipment. Take precautionary measures against static discharge.

Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed. Keep in an area equipped with solvent resistant flooring.

Incompatible materials : Store away from incompatible materials. Copper. Plastic materials.

Heat and ignition sources : The vapour may be invisible, heavier than air and spread along ground. Can form explosive mixture with air.

Information on mixed storage : Keep away from food, drink and animal feedingstuffs.

Storage area : Store away from heat.

Packaging materials : Keep only in the original container in a cool, well-ventilated place away from combustible materials. Mild steel. Stainless steel. Aluminium. polyethylene container.

#### Germany

Storage class (LGK, TRGS 510)

Joint storage table

: LGK 3 - Flammable liquids

LGK 1	LGK 2A	LGK 2B	LGK 3	LGK 4.1A
LGK 4.1B	LGK 4.2	LGK 4.3	LGK 5.1A	LGK 5.1B
LGK 5.1C	LGK 5.2	LGK 6.1A	LGK 6.1B	LGK 6.1C
LGK 6.1D	LGK 6.2	LGK 7	LGK 8A	LGK 8B
LGK 10	LGK 11	LGK 12	LGK 13	LGK 10-13

Joint storage not permitted for

: LGK 1, LGK 2A, LGK 4.1A, LGK 4.1B, LGK 4.2, LGK 4.3, LGK 5.1A, LGK 5.1C, LGK 5.2, LGK 6.1B, LGK 6.2, LGK 7

Joint storage with restrictions permitted for

: LGK 5.1B, LGK 6.1D, LGK 11, LGK 10-13

Joint storage permitted for

: LGK 2B, LGK 3, LGK 6.1A, LGK 6.1C, LGK 8A, LGK 8B, LGK 10, LGK 12, LGK 13

#### Switzerland

Storage class (LK)

: LK 3 - Flammable liquids

### 7.3. Specific end use(s)

No additional information available

# N-Butyl Acetate

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

No additional information available

#### 8.2. Exposure controls

##### Appropriate engineering controls

##### Appropriate engineering controls:

Ensure good ventilation of the work station. Provide sufficient air exchange and/or exhaust.

##### Personal protection equipment

##### Personal protective equipment symbol(s):



##### Eye and face protection

##### Eye protection:

Safety glasses

Eye protection			
Type	Field of application	Characteristics	Standard
Safety glasses, Safety goggles	Dust, Fine dust, Liquid, Droplet, spray	With side shields	EN 166

##### Skin protection

##### Skin and body protection:

Wear suitable protective clothing

##### Hand protection:

Protective gloves. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Protective gloves should be replaced at first signs of wear.

Hand protection					
Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Disposable gloves	Nitrile rubber (NBR), Butyl rubber, Polyvinylchloride (PVC), Viton	5 (> 240 minutes)	0.44		EN ISO 374

##### Respiratory protection

##### Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

Respiratory protection			
Device	Filter type	Condition	Standard
Aerosol mask	Filter AX (brown)	Vapour protection, Protection for Liquid particles	EN 14387

##### Environmental exposure controls

##### Environmental exposure controls:

Avoid release to the environment.

# N-Butyl Acetate

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Not available
Appearance	: Colourless liquid.
Molecular mass	: 116.16 g/mol
Odour	: Fruity.
Odour threshold	: 7 – 20 ppm
Melting point	: < -90 °C (1013 hPa)
Freezing point	: Not available
Boiling point	: 126 °C (1013 hPa)
Flammability	: Not applicable
Explosive properties	: Explosive vapour/air mixtures may be formed.
Oxidising properties	: Not oxidising.
Lower explosion limit	: 1.2 vol %
Upper explosion limit	: 15 vol %
Flash point	: 27 °C (1013 hPa)
Auto-ignition temperature	: 415 °C (DIN 51794)
Decomposition temperature	: Not available
pH	: 6.2 (5 g/l ; 2 °C)(as aqueous solution)
Viscosity, kinematic	: 0.83 mm <sup>2</sup> /s (20 °C)
Viscosity, dynamic	: 0.73 mPa·s (20 °C) (ASTM D 445)
Solubility	: Water: 5.3 g/l (20 °C) (OECD Test Guideline 105)
Partition coefficient n-octanol/water (Log Kow)	: 2.3 (25 °C) (OECD Test Guideline 117)
Vapour pressure	: 15 hPa (20 °C)
Vapour pressure at 50°C	: 63 hPa(a)
Density	: 0.88 g/cm <sup>3</sup> (20 °C)
Relative density	: 0.8812
Relative vapour density at 20°C	: 4 (Air = 1.0)
Particle characteristics	: Not applicable

#### 9.2. Other information

##### Other safety characteristics

Relative evaporation rate (ether=1)	: 12
Surface tension	: 61.3 mN/m (1 g/l; 20 °C) (OECD Test Guideline 115)

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

Extremely flammable liquid and vapour.

#### 10.2. Chemical stability

Stable under normal conditions.

#### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

#### 10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

#### 10.5. Incompatible materials

Combustible materials. Oxidizing agent. Strong acids. Strong bases.

#### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

# N-Butyl Acetate

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### SECTION 11: Toxicological information

#### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified
Skin corrosion/irritation	: Not classified
	pH: 6.2 (5 g/l ; 2 °C)(as aqueous solution)
Serious eye damage/irritation	: Not classified
	pH: 6.2 (5 g/l ; 2 °C)(as aqueous solution)
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: May cause drowsiness or dizziness.
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified

<b>N-Butyl Acetate (123-86-4)</b>	
Viscosity, kinematic	0.83 mm <sup>2</sup> /s (20 °C)

#### 11.2. Information on other hazards

No additional information available

### SECTION 12: Ecological information

#### 12.1. Toxicity

Ecology - general	: The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Not classified

#### 12.2. Persistence and degradability

<b>N-Butyl Acetate (123-86-4)</b>	
Persistence and degradability	Not rapidly degradable

#### 12.3. Bioaccumulative potential

<b>N-Butyl Acetate (123-86-4)</b>	
Partition coefficient n-octanol/water (Log Kow)	2.3 (25 °C) (OECD Test Guideline 117)

#### 12.4. Mobility in soil

<b>N-Butyl Acetate (123-86-4)</b>	
Surface tension	61.3 mN/m (1 g/l; 20 °C) (OECD Test Guideline 115)

#### 12.5. Results of PBT and vPvB assessment

<b>N-Butyl Acetate (123-86-4)</b>	
This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII	
This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII	

# N-Butyl Acetate

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 12.6. Endocrine disrupting properties

No additional information available

### 12.7. Other adverse effects

No additional information available






## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

- Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions. Disposal together with normal waste is not allowed.
- Product/Packaging disposal recommendations : Special disposal required according to local regulations. Do not let product enter drains. Contact waste disposal services. This product shall be disposed of or recovered in compliance with Directive 2008/98/EC on waste as lastly amended.
- Additional information : Flammable vapours may accumulate in the container.
- HP Code : HP3 - "Flammable:"  
– flammable liquid waste: liquid waste having a flash point below 60 °C or waste gas oil, diesel and light heating oils having a flash point > 55 °C and ≤ 75 °C;  
– flammable pyrophoric liquid and solid waste: solid or liquid waste which, even in small quantities, is liable to ignite within five minutes after coming into contact with air;  
– flammable solid waste: solid waste which is readily combustible or may cause or contribute to fire through friction;  
– flammable gaseous waste: gaseous waste which is flammable in air at 20 °C and a standard pressure of 101.3 kPa;  
– water reactive waste: waste which, in contact with water, emits flammable gases in dangerous quantities;  
– other flammable waste: flammable aerosols, flammable self-heating waste, flammable organic peroxides and flammable self-reactive waste.

## SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
<b>14.1. UN number or ID number</b>				
UN 1123	UN 1123	UN 1123	UN 1123	UN 1123
<b>14.2. UN proper shipping name</b>				
BUTYL ACETATES	BUTYL ACETATES	Butyl acetates	BUTYL ACETATES	BUTYL ACETATES
<b>Transport document description</b>				
UN 1123 BUTYL ACETATES, 3, III, (D/E)	UN 1123 BUTYL ACETATES, 3, III	UN 1123 Butyl acetates, 3, III	UN 1123 BUTYL ACETATES, 3, III	UN 1123 BUTYL ACETATES, 3, III
<b>14.3. Transport hazard class(es)</b>				
3	3	3	3	3
				
<b>14.4. Packing group</b>				
III	III	III	III	III

# N-Butyl Acetate



## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ADR	IMDG	IATA	ADN	RID
<b>14.5. Environmental hazards</b>				
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No EmS-No. (Fire): F-E EmS-No. (Spillage): S-D	Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No
No supplementary information available				

### 14.6. Special precautions for user

#### Overland transport

Classification code (ADR)	: F1
Limited quantities (ADR)	: 5I
Excepted quantities (ADR)	: E1
Packing instructions (ADR)	: P001, IBC03, LP01, R001
Mixed packing provisions (ADR)	: MP19
Portable tank and bulk container instructions (ADR)	: T2
Portable tank and bulk container special provisions (ADR)	: TP1
Tank code (ADR)	: LGBF
Vehicle for tank carriage	: FL
Transport category (ADR)	: 3
Special provisions for carriage - Packages (ADR)	: V12
Special provisions for carriage - Operation (ADR)	: S2
Hazard identification number (Kemler No.)	: 30
Orange plates	:  
Tunnel restriction code (ADR)	: D/E
EAC code	: 3Y

#### Transport by sea

Special provisions (IMDG)	: 223
Limited quantities (IMDG)	: 5 L
Excepted quantities (IMDG)	: E1
Packing instructions (IMDG)	: P001, LP01
IBC packing instructions (IMDG)	: IBC03
Tank instructions (IMDG)	: T2
Tank special provisions (IMDG)	: TP1
Stowage category (IMDG)	: A
Properties and observations (IMDG)	: Colourless liquids with a pineapple-like odour. Immiscible with water. normal-BUTYL ACETATE: flashpoint 27°C c.c. Explosive limits: 1.5% to 15%.

#### Air transport

PCA Excepted quantities (IATA)	: E1
PCA Limited quantities (IATA)	: Y344
PCA limited quantity max net quantity (IATA)	: 10L
PCA packing instructions (IATA)	: 355
PCA max net quantity (IATA)	: 60L
CAO packing instructions (IATA)	: 366
CAO max net quantity (IATA)	: 220L
Special provisions (IATA)	: A3
ERG code (IATA)	: 3L

#### Inland waterway transport

Classification code (ADN)	: F1
Limited quantities (ADN)	: 5 L
Excepted quantities (ADN)	: E1

# N-Butyl Acetate

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Carriage permitted (ADN)	: T
Equipment required (ADN)	: PP, EX, A
Ventilation (ADN)	: VE01
Number of blue cones/lights (ADN)	: 0

### Rail transport

Classification code (RID)	: F1
Limited quantities (RID)	: 5L
Excepted quantities (RID)	: E1
Packing instructions (RID)	: P001, IBC03, LP01, R001
Mixed packing provisions (RID)	: MP19
Portable tank and bulk container instructions (RID)	: T2
Portable tank and bulk container special provisions (RID)	: TP1
Tank codes for RID tanks (RID)	: LGBF
Transport category (RID)	: 3
Special provisions for carriage – Packages (RID)	: W12
Colis express (express parcels) (RID)	: CE4
Hazard identification number (RID)	: 30

### 14.7. Maritime transport in bulk according to IMO instruments

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU-Regulations

##### REACH Annex XVII (Restriction List)

Not listed on REACH Annex XVII

##### REACH Annex XIV (Authorisation List)

Not listed on REACH Annex XIV (Authorisation List)

##### REACH Candidate List (SVHC)

Not listed on the REACH Candidate List

##### PIC Regulation (Prior Informed Consent)

Not listed on the PIC list (Regulation EU 649/2012)

##### POP Regulation (Persistent Organic Pollutants)

Not listed on the POP list (Regulation EU 2019/1021)

##### Ozone Regulation (2024/590)

Not listed on the Ozone Depletion list (Regulation EU 2024/590)

##### Council Regulation (EC) for the control of dual-use items

Not listed on the COUNCIL REGULATION (EC) of dual-use items.

##### Explosives Precursors Regulation (EU 2019/1148)

Not listed on the Explosives Precursors list (EU)

##### Drug Precursors Regulation (EC 273/2004)

Not listed on the Drug Precursors list (EU)

#### National regulations

##### Austria

Ordinance on Flammable Liquids (VbF) : Hazard category 3: Flammable (flash point 23 - 60 °C. Excluding gas oils and petroleum).  
Toxic Substances Ordinance 2000 : Is not subject to the Toxic Substances Ordinance 2000.

##### Denmark

Class for fire hazard : Class II-1

# N-Butyl Acetate

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Store unit	: 5 liter
Classification remarks	: R10 <H226;H336>; Emergency management guidelines for the storage of flammable liquids must be followed
Danish National Regulations	: Young people below the age of 18 years are not allowed to use the product Pregnant/breastfeeding women working with the product must not be in direct contact with it. If an employee is pregnant or breastfeeding and the person in question uses or is exposed to this product at work, the employer must always carry out a risk assessment of the work. The assessment must both deal with the dangerousness of the impact and its strength and duration. The employer's decision that a pregnant or lactating woman can perform a specific work task must therefore be made in the context of her specific working conditions. See also WEA-Guideline A.1.8-7 on the working environment of pregnant and breastfeeding workers. Listed or contains substance(s) on the Denmark - Indicative list of organic solvents present in Annex 3.4.1 of the WEA Guidance C.0.1-1: Butyl acetate, all isomers (123-86-4)

### Finland

### France

Occupational diseases	
Code	Description
RG 84	Conditions caused by liquid organic solvents for professional use: saturated or unsaturated aliphatic or cyclic liquid hydrocarbons and mixtures thereof; liquid halogenated hydrocarbons; nitrated derivatives of aliphatic hydrocarbons; alcohols; glycols, glycol ethers; ketones; aldehydes; aliphatic and cyclic ethers, including tetrahydrofuran; esters; dimethylformamide and dimethylacetamine; acetonitrile and propionitrile; pyridine; dimethylsulfone and dimethylsulfoxide

### Germany

Employment restrictions	: Observe restrictions according Act on the Protection of Working Mothers (MuSchG). Observe restrictions according Act on the Protection of Young People in Employment (JArbSchG).
Water hazard class (WGK)	: WGK 1, Slightly hazardous to water (Classification according to AwSV; ID No. 42).
Major Accidents Ordinance (12. BImSchV)	: Is listed in the Major Accidents Ordinance (12. BImSchV)

Major Accidents Ordinance (12. BImSchV)				
Number	Code	Title	Lower-tier	Upper-tier
1.2.5.1	P5a	Flammable liquids. Flammable liquids of category 1; flammable liquids of category 2 or 3 maintained at a temperature above their boiling point; other liquids with a flash point of $\leq 60$ °C maintained at a temperature above their boiling point	10,000 kg	50,000 kg
1.2.5.2	P5b	Flammable liquids. Flammable liquids of category 2 or 3, where special processing conditions such as high pressure or high temperature can lead to the risk of accidents; other liquids with a flash point of $\leq 60$ °C, where special processing conditions such as high pressure or high temperature can lead to the risk of accidents	50,000 kg	200,000 kg
1.2.5.3	P5c	Flammable liquids of categories 2 or 3, not covered under P5a and P5b	5,000,000 kg	50,000,000 kg

### Netherlands

ABM category	: B(4) - low hazard for aquatic organisms
SZW-lijst van kankerverwekkende stoffen	: The substance is not listed
SZW-lijst van mutagene stoffen	: The substance is not listed
SZW-lijst van reprotoxische stoffen – Borstvoeding	: The substance is not listed
SZW-lijst van reprotoxische stoffen – Vruchtbaarheid	: The substance is not listed
SZW-lijst van reprotoxische stoffen – Ontwikkeling	: The substance is not listed

# N-Butyl Acetate

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### Poland

#### Polish National Regulations

- : Act of 25 February 2011 on chemical substances and their mixtures (J. o L. No. 63, item 322 as amended; consolidated text J. o L. 2019, item 1225).  
Act of 14 December 2012 on waste (J. o L. 2013, item 322 as amended; consolidated text J. o L. 2020, item 797).  
The announcement of Marshal of the Sejm of the Republic of Poland dated 19 October 2016 concerning the consolidated text announcement of the decree on the management of packaging and packaging waste (J. o L. 2016, item 1863 as amended).  
Decree of the Minister of Environment of 14 December 2014 on the catalogue of waste (J. o L. 2014, item 1923).  
Act of 19 August 2011 on the Carriage of Dangerous Goods (J. o L. 2011 No. 227, item 1367 as amended; consolidated text J. o L. 2020, item 154).  
Regulation of the Minister of Family, Labour and Social Policy of 12 June 2018 on the highest permissible concentration and intensity of noxious agents for health at work environment (J. o L. item 1286 as amended).  
The announcement of Minister of Health dated 9 September 2016 concerning the consolidated text announcement of the decree of the Minister of Health of 30 December 2004 on health and safety at work related to exposure to chemical agents at work (J. o L. of 16 September 2016, item 1488)  
Regulation of the Minister of Health of 2 February 2011 on tests and measurements of the noxious agents for health at work environment (J. o L. No. 33, item 166 as amended).  
Regulation of the Minister of Environment of 9 December 2003 on particularly hazardous substances to the environment (J. o L. No. 217, item 2141).  
ADR Agreement: Government Statement of 13 March 2023 on the entry into force of amendments to Annexes A and B to the Agreement concerning the International Carriage of Dangerous Goods by Road (ADR), signed in Geneva on 30 September 1957 (J. o. L. 2023, item 891)  
Regulation of the Minister of Health of 25 August 2015 on the method of marking places, pipelines, and containers and tanks used for storing or containing hazardous substances or hazardous mixtures (J.o.L. 2015, item 1368 as amended)

### Spain

#### Royal Decree 665/1997

- : Is not subject to the Royal Decree 665/1997

## 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

## SECTION 16: Other information

### Abbreviations and acronyms:

ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer

# N-Butyl Acetate

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Abbreviations and acronyms:	
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstracts Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disruptor

Full text of H- and EUH-statements:	
Flam. Liq. 3	Flammable liquids, Category 3
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis
H226	Flammable liquid and vapour.
H336	May cause drowsiness or dizziness.
EUH066	Repeated exposure may cause skin dryness or cracking.

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.