

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Product form : Mixture
Product name : Red Antifreeze
Product code : VC271

1.2. Relevant identified uses of the substance or mixture and uses advised against**1.2.1. Relevant identified uses**

Intended for general public
Main use category : Professional use, Industrial use, Consumer use
Use of the substance/mixture : Cleaning/washing agents and additives

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Valet-Chem Ltd
Summit Close
NG17 8GJ Kirkby In Ashfield Nottingham, Nottinghamshire
United Kingdom
T +44 (0) 844 414 0987
info@valetchem.co.uk

1.4. Emergency telephone number

Emergency number : +44 (0) 844 414 0987

Country/Area	Organisation/Company	Address	Emergency number	Comment
United Kingdom	National Poisons Information Service (Birmingham Centre) City Hospital	Dudley Road B18 7QH	0344 892 0111	Only for healthcare professionals
United Kingdom	National Poisons Information Service (Cardiff Centre) University Hospital Llandough	Penlan Road CF64 2XX	0344 892 0111	Only for healthcare professionals
United Kingdom	Guy's & St Thomas' Poisons Unit Medical Toxicology Unit, Guy's & St Thomas' Hospital Trust	Avonley Road SE14 5ER	+44 20 7188 7188	
United Kingdom	National Poisons Information Service (Belfast Centre) Royal Victoria Hospital	Grosvenor Road BT12 6BA	0344 892 0111	Only for healthcare professionals
United Kingdom	NHS 111/NHS 24/NHS Direct		111 0845 4647	or call a doctor

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Classification according to Regulation (EC) No. 1272/2008 [CLP]**

Acute toxicity (oral), Category 4 H302
Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

Harmful if swallowed.

Red Antifreeze

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS07

Signal word (CLP) :

Warning

Contains :

ETHYLENE GLYCOL; 2-ETHYLHEXANOIC ACID, SODIUM SALT

Hazard statements (CLP) :

H302 - Harmful if swallowed.

Precautionary statements (CLP) :

P102 - Keep out of reach of children.

P264 - Wash hands, forearms and face thoroughly after handling.

P270 - Do not eat, drink or smoke when using this product.

P301+P312 - IF SWALLOWED: Call a POISON CENTRE or doctor if you feel unwell.

P330 - Rinse mouth.

P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards

Contains no PBT/vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
ETHYLENE GLYCOL substance with a Community workplace exposure limit	CAS-No.: 107-21-1 EC-No.: 203-473-3 EC Index-No.: 603-027-00-1	>30	Acute Tox. 4 (Oral), H302 STOT RE 2, H373
2-ETHYLHEXANOIC ACID, SODIUM SALT	CAS-No.: 19766-89-3 EC-No.: 243-283-8	<5	Acute Tox. 4 (Oral), H302 STOT RE 2, H373

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general :

Call a poison center or a doctor if you feel unwell.

First-aid measures after inhalation :

Remove person to fresh air and keep comfortable for breathing.

First-aid measures after skin contact :

Wash skin with plenty of water.

First-aid measures after eye contact :

Rinse eyes with water as a precaution.

First-aid measures after ingestion :

Rinse mouth. Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation :

Although no appropriate human or animal health effects data are known to exist, this material is expected to be an inhalation hazard.

Symptoms/effects after skin contact :

None under normal conditions.

Red Antifreeze

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Symptoms/effects after eye contact : None under normal conditions.
Symptoms/effects after ingestion : None under normal conditions.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard : No fire hazard.
Explosion hazard : No direct explosion hazard.
Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Advice for firefighters

Firefighting instructions : Fight fire from safe distance and protected location. Do not enter fire area without proper protective equipment, including respiratory protection.
Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Stop leak if safe to do so. Notify authorities if product enters sewers or public waters.
Absorb spillage to prevent material damage.

6.1.1. For non-emergency personnel

Protective equipment : Wear recommended personal protective equipment.
Emergency procedures : Ventilate spillage area.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures : Evacuate unnecessary personnel. Stop leak if safe to do so.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Absorb spilled material with sand or earth. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak without risks if possible.
Methods for cleaning up : Take up liquid spill into absorbent material.
Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Not expected to present a significant hazard under anticipated conditions of normal use.
Precautions for safe handling : Ensure good ventilation of the work station. Wear personal protective equipment.

Red Antifreeze

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Keep in a cool, well-ventilated place away from heat.
Storage conditions : Keep cool. Protect from sunlight.
Packaging materials : Store always product in container of same material as original container.

Switzerland

Storage class (LK) : LK 10/12 - Liquids

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

ETHYLENE GLYCOL (107-21-1)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Ethylene glycol
IOEL TWA	20 ppm
IOEL STEL	104 mg/m ³
	40 ppm
Remark	Skin
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
Austria - Occupational Exposure Limits	
Local name	Ethylenglykol (Ethandiol; Glykol)
MAK (OEL TWA)	26 mg/m ³
	10 ppm
MAK (OEL STEL)	52 mg/m ³ (8x 5(Mow) min)
	20 ppm (8x 5(Mow) min)
Remark	H
Regulatory reference	BGBl. II Nr. 156/2021
Belgium - Occupational Exposure Limits	
Local name	Ethylèneglycol (en aérosol) # Ethyleenglycol
OEL TWA	52 mg/m ³
	20 ppm
OEL STEL	104 mg/m ³
	40 ppm

Red Antifreeze

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ETHYLENE GLYCOL (107-21-1)	
Remark	D: la mention "D" signifie que la résorption de l'agent, via la peau, les muqueuses ou les yeux, constitue une partie importante de l'exposition totale. Cette résorption peut se faire tant par contact direct que par présence de l'agent dans l'air, M: la mention "M" indique que lors d'une exposition supérieure à la valeur limite, des irritations apparaissent ou un danger d'intoxication aiguë existe. Le procédé de travail doit être conçu de telle façon que l'exposition ne dépasse jamais la valeur limite. Lors des mesurages, la période d'échantillonnage doit être aussi courte que possible afin de pouvoir effectuer des mesurages fiables. Le résultat des mesurages est calculé en fonction de la période d'échantillonnage. # D: de vermelding "D" betekent dat de opname van het agens via de huid, de slijmvliezen of de ogen een belangrijk deel van de totale blootstelling vormt. Deze opname kan het gevolg zijn van zowel direct contact als zijn aanwezigheid in de lucht, M: de vermelding "M" duidt aan dat bij de blootstelling boven de grenswaarde irritatie optreedt of er gevaar bestaat voor acute vergiftiging. Het werkprocédé moet zo zijn ontworpen dat de blootstelling de grenswaarde nooit overschrijdt. Bij een controle geldt dat de bemonsterde periode zo kort mogelijk moet zijn om een betrouwbare meting te kunnen verrichten. Het meetresultaat wordt dan gerelateerd aan de beschouwde periode.
Regulatory reference	Koninklijk besluit/Arrêté royal 19/11/2020
Bulgaria - Occupational Exposure Limits	
Local name	Етиленгликол
OEL TWA	52 mg/m ³ 20 ppm
OEL STEL	104 mg/m ³ 40 ppm
Remark	Кожа (възможна е значителна резорбция чрез кожата); • (Химични агенти, за които са определени гранични стойности във въздуха на работната среда за Европейската общност)
Regulatory reference	Наредба № 13 от 30.12.2003 г. за защита на работещите от рискове, свързани с експозиция на химични агенти при работа (изм. и доп. ДВ. бр. 47 от 2021 г., в сила от 04.06.2021 г.)
Croatia - Occupational Exposure Limits	
Local name	Etandiol; etilen-glikol
GVI (OEL TWA)	52 mg/m ³ 20 ppm
KGVI (OEL STEL)	104 mg/m ³ 40 ppm
Remark	Direktiva: 2000/39/EZ. Napomena: Koža (razvrstana kao tvar koja nadražuje kožu (H315))
Regulatory reference	Pravilnik o izmjenama i dopunama Pravilnika o graničnim vrijednostima izloženosti opasnim tvarima pri radu i o biološkim graničnim vrijednostima (NN 1/2021)
Cyprus - Occupational Exposure Limits	
Local name	Αιθυλενογλυκόλη
OEL TWA	52 mg/m ³ 20 ppm
OEL STEL	104 mg/m ³ 40 ppm
Remark	δέρμα
Regulatory reference	Κανονισμοί του 2007 (Κ.Δ.Π. 295/2007)

Red Antifreeze

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ETHYLENE GLYCOL (107-21-1)	
Czech Republic - Occupational Exposure Limits	
Local name	Ethylenglykol (Ethan-1,2-diol)
PEL (OEL TWA)	50 mg/m ³
	20 ppm
NPK-P (OEL C)	100 mg/m ³
	39 ppm
Remark	D - při expozici se významně uplatňuje pronikání faktoru kůží.
Regulatory reference	Nařízení vlády č. 361/2007 Sb. (Předpis 195/2021 Sb.)
Denmark - Occupational Exposure Limits	
Local name	Ethylenglycol (1,2-Ethandiol; Glycol)
OEL TWA	26 mg/m ³
	10 mg/m ³ forstøvet
	10 ppm
Remark	E (betyder, at stoffet har en EF-grænseværdi); H (betyder, at stoffet kan optages gennem huden)
Regulatory reference	BEK nr 1426 af 28. juni 2021
Estonia - Occupational Exposure Limits	
Local name	1,2-etaandiool (etüleenglükool)
OEL TWA	52 mg/m ³
	20 ppm
OEL STEL	104 mg/m ³
	40 ppm
Remark	A (Naha kaudu kergesti imenduv aine), 18 (Piirnorm kehtib auru ja aerosooli summaarse sisalduse kohta)
Regulatory reference	Vabariigi Valitsuse 20. märtsi 2001. a määruse nr 105 (RT I, 17.10.2019, 2); Vabariigi Valitsuse 10. märtsi 2019. a määruse nr 84
Finland - Occupational Exposure Limits	
Local name	1,2-Etaanidioli
HTP (OEL TWA)	50 mg/m ³
	20 ppm
HTP (OEL STEL)	100 mg/m ³
	40 ppm
Remark	Iho
Regulatory reference	HTP-ARVOT 2020 (Sosiaali- ja terveysministeriö)
France - Occupational Exposure Limits	
Local name	Ethylèneglycol (vapeur)
VME (OEL TWA)	52 mg/m ³
	20 ppm
VLE (OEL C/STEL)	104 mg/m ³
	40 ppm

Red Antifreeze

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ETHYLENE GLYCOL (107-21-1)	
Remark	Valeurs réglementaires indicatives; risque de pénétration percutanée
Regulatory reference	Arrêté du 30 juin 2004 modifié (réf.: INRS ED 984, 2016)
Germany - Occupational Exposure Limits (TRGS 900)	
AGW (OEL TWA)	26 mg/m ³ 10 ppm
Peak exposure limitation factor	2(I)
Remark	DFG - Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe der DFG (MAK-Kommission); EU - Europäische Union (Von der EU wurde ein Luftgrenzwert festgelegt: Abweichungen bei Wert und Spitzenbegrenzung sind möglich); H - hautresorptiv; Y - Ein Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes (BGW) nicht befürchtet zu werden; 11 - Summe aus Dampf und Aerosolen
Regulatory reference	TRGS900
Gibraltar - Occupational Exposure Limits	
Local name	Ethylene glycol
OEL TWA	52 mg/m ³ 20 ppm
OEL STEL	104 mg/m ³ 40 ppm
Remark	Skin
Regulatory reference	Factories (Control of Chemical Agents at Work) Regulations 2003 (LN. 2018/181)
Greece - Occupational Exposure Limits	
Local name	Αιθυλενογλυκόλη (σπμολί)
OEL TWA	125 mg/m ³ 50 ppm
OEL STEL	125 mg/m ³ 50 ppm
Regulatory reference	Π.Δ. 90/1999 - Προστασία της υγείας των εργαζομένων που εκτίθενται σε ορισμένους χημικούς παράγοντες κατά τη διάρκεια της εργασίας τους
Hungary - Occupational Exposure Limits	
Local name	ETILÉNGLIKOL
AK (OEL TWA)	52 mg/m ³
CK (OEL STEL)	104 mg/m ³
Remark	b (Bőrön át is felszívódik), i (ingerlő anyag, amely izgatja a bőrt, nyálkahártyát, szemet vagy mindhármát); EU1 (2000/39/EK irányelvben közölt érték); N (Irritáló anyagok, egyszerű fojtógázok, csekély egészségkárosító hatással bíró anyagok)
Regulatory reference	5/2020. (II. 6.) ITM rendelet - A kémiai kóroki tényezők hatásának kitett munkavállalók egészségének és biztonságának védelméről
Ireland - Occupational Exposure Limits	
Local name	Ethane-1,2-diol [Ethylene glycol]
OEL TWA	10 mg/m ³ particulate 52 mg/m ³ vapour

Red Antifreeze

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ETHYLENE GLYCOL (107-21-1)	
	20 ppm vapour
OEL STEL	104 mg/m ³ vapour
	40 ppm vapour
Remark	Sk (Substances which have the capacity to penetrate intact skin when they come in contact with it, and be absorbed into the body), IOELV (Indicative Occupational Exposure Limit Values)
Regulatory reference	Chemical Agents Code of Practice 2021
Italy - Occupational Exposure Limits	
Local name	Etilen glicol
OEL TWA	52 mg/m ³
	20 ppm
OEL STEL	104 mg/m ³
	40 ppm
Remark	Cute
Regulatory reference	Allegato XXXVIII del D.Lgs. 9 aprile 2008, n. 81 e s.m.i.
Latvia - Occupational Exposure Limits	
Local name	Etilēnglikols, (1,2-etāndiols)
OEL TWA	52 mg/m ³
	20 ppm
OEL STEL	104 mg/m ³
	40 ppm
Remark	Āda
Regulatory reference	Ministru kabineta 2007. gada 15. maija noteikumiem Nr. 325
Lithuania - Occupational Exposure Limits	
Local name	Etilēnglikolis (1,2-etāndiolis, glikolis)
IPRV (OEL TWA)	25 mg/m ³
	10 ppm
TPRV (OEL STEL)	50 mg/m ³
	20 ppm
Remark	O (medžiaga į organizmą gali prasiskverbti pro nepažeistą odą); Šis RD taikomas bendrai garų ir aerozolio koncentracijai.
Regulatory reference	LIETUVOS HIGIENOS NORMA HN 23:2011 (Nr. V-695/A1-272, 2018-06-12)
Luxembourg - Occupational Exposure Limits	
Local name	Éthylène-glycol
OEL TWA	52 mg/m ³
	20 ppm
OEL STEL	104 mg/m ³
	40 ppm
Remark	Peau

Red Antifreeze

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ETHYLENE GLYCOL (107-21-1)	
Regulatory reference	Mémorial A N° 226 de 2021 concernant la protection de la sécurité et de la santé des salariés contre les risques liés à des agents chimiques sur le lieu de travail
Malta - Occupational Exposure Limits	
Local name	Ethylene glycol
OEL TWA	52 mg/m ³
	20 ppm
OEL STEL	104 mg/m ³
	40 ppm
Remark	Skin # Ġilda
Regulatory reference	S.L.424.24 - Chemical Agents at Work Regulations (L.N.57 of 2018)
Netherlands - Occupational Exposure Limits	
Local name	Ethaan-1,2-diol
TGG-8u (OEL TWA)	52 mg/m ³ (damp)
	10 mg/m ³ (druppels)
TGG-15min (OEL STEL)	104 mg/m ³ (damp)
Remark	H (Huidopname) Stoffen die relatief gemakkelijk door de huid kunnen worden opgenomen, hetgeen een substantiële bijdrage kan betekenen aan de totale inwendige blootstelling, hebben in de lijst een H-aanduiding. Bij deze stoffen moeten naast maatregelen tegen inademing ook adequate maatregelen ter voorkoming van huidcontact worden genomen.
Regulatory reference	Arbeidsomstandighedenregeling 2021
Poland - Occupational Exposure Limits	
Local name	Glikol etylenowy
NDS (OEL TWA)	15 mg/m ³
NDSch (OEL STEL)	50 mg/m ³
Remark	Skóra (Oznakowanie substancji notacją „skóra” oznacza, że wchłanianie substancji przez skórę może być tak samo istotne jak przy narażeniu drogą oddechową).
Regulatory reference	Dz. U. 2018 poz. 1286
Portugal - Occupational Exposure Limits	
Local name	Etilenoglicol
OEL C	100 ppm H (Apenas aerosol)
Remark	A4 (Agente não classificável como carcinogénico no Homem)
Regulatory reference	Norma Portuguesa NP 1796:2014
Romania - Occupational Exposure Limits	
Local name	Etilenglicol/Etandiol
OEL TWA	52 mg/m ³
	20 ppm
OEL STEL	104 mg/m ³
	40 ppm
Remark	P - posibilitatea unei penetrări cutanate importante
Regulatory reference	Hotărârea Guvernului nr. 1.218/2006 (Hotărârea nr. 53/2021)

Red Antifreeze

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ETHYLENE GLYCOL (107-21-1)	
Serbia - Occupational Exposure Limits	
Local name	етилен гликол; етандиол
OEL TWA	52 mg/m ³
	20 ppm
OEL STEL	104 mg/m ³
	40 ppm
Remark	EU* – напомена да се ради о хемијским материјама за које су утврђене индикативне граничне вредности изложености према Директиви 2000/39/ЕЗ (прва листа); К – напомена да хемијска материја може штетно деловати на кожу
Regulatory reference	ПРАВИЛНИК о превентивним мерама за безбедан и здрав рад при излагању хемијским материјама („Службени гласник РС”, бр. 106/09 и 117/17)
Slovakia - Occupational Exposure Limits	
Local name	Etylén glykol (etán-1,2-diol)
NPHV (OEL TWA)	52 mg/m ³
	20 ppm
NPHV (OEL STEL)	104 mg/m ³
	40 ppm
Remark	K - znamená, že faktor môže byť ľahko absorbovaný kožou
Regulatory reference	Nariadenie vlády č. 355/2006 Z. z. (236/2020 Z. z.)
Slovenia - Occupational Exposure Limits	
Local name	etandiol (glikol)
OEL TWA	52 mg/m ³
	20 ppm
OEL STEL	104 mg/m ³
	40 ppm
Remark	K (Lastnost lažjega prehajanja snovi v organizem skozi kožo), Y (Snovi, pri katerih ni nevarnosti za zarodek ob upoštevanju mejnih vrednosti in bat vrednosti), EU
Regulatory reference	Uradni list RS, št. 72/2021 z dne 11.5.2021
Spain - Occupational Exposure Limits	
Local name	Etilenglicol
VLA-ED (OEL TWA)	52 mg/m ³
	20 ppm
VLA-EC (OEL STEL)	104 mg/m ³
	40 ppm
Remark	Vía dérmica (Indica que, en las exposiciones a esta sustancia, la aportación por la vía cutánea puede resultar significativa para el contenido corporal total si no se adoptan medidas para prevenir la absorción. En estas situaciones, es aconsejable la utilización del control biológico para poder cuantificar la cantidad global absorbida del contaminante), VLI (Agente químico para el que la U.E. estableció en su día un valor límite indicativo).
Regulatory reference	Límites de Exposición Profesional para Agentes Químicos en España 2021. INSHT
Sweden - Occupational Exposure Limits	
Local name	Etylenglykol (Glykol)

Red Antifreeze

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ETHYLENE GLYCOL (107-21-1)	
NGV (OEL TWA)	25 mg/m ³
	10 ppm
KTV (OEL STEL)	104 mg/m ³
	40 ppm
Remark	H (Ämnet kan lätt upptas genom huden. Det föreskrivna gränsvärdet bedöms ge tillräckligt skydd endast under förutsättning att huden är skyddad mot exponering för ämnet ifråga); 26 (Gränsvärdet gäller den sammanlagda koncentrationen av ånga och aerosol)
Regulatory reference	Hygieniska gränsvärden (AFS 2018:1)
United Kingdom - Occupational Exposure Limits	
Local name	Ethane-1,2-diol
WEL TWA (OEL TWA)	52 mg/m ³ VAPOUR
	20 ppm VAPOUR
WEL STEL (OEL STEL)	104 mg/m ³ VAPOUR
	40 ppm VAPOUR
Remark	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
Iceland - Occupational Exposure Limits	
Local name	Etýlenglykól (1,2-etandíól, glykól, mónóetýlenglykól)
OEL TWA	26 mg/m ³
	26 mg/m ³ úði
	10 ppm úði
	10 ppm
OEL STEL	104 mg/m ³
	40 ppm
Remark	H (efnið getur auðveldlega borist inn í líkamann gegnum húð)
Regulatory reference	Reglugerð um mengunarmörk og aðgerðir til að draga úr mengun á vinnustöðum (Nr. 1296/2012)
Norway - Occupational Exposure Limits	
Local name	1,2-ethandiol (Etylenglykol)
Grenseverdi (OEL TWA)	52 mg/m ³
	20 ppm
Korttidsverdi (OEL STEL)	104 mg/m ³
	40 ppm
Remark	H: Kjemikalier som kan tas opp gjennom huden; E: EU har en veiledende grenseverdi og/eller anmerkning for stoffet; 5) Grenseverdien er basert på beregning av summen av gass- og partikkelform (aerosol) av stoffet.
Regulatory reference	FOR-2021-06-28-2248
North Macedonia - Occupational Exposure Limits	
Local name	етандиол (гликол)
OEL TWA	52 mg/m ³
	20 ppm

Red Antifreeze

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ETHYLENE GLYCOL (107-21-1)	
KTV	2
Short time value [mg/m ³]	104 mg/m ³
Short time value [ppm]	40 ppm
Remark	(KTV) краткотрајна вредност (КТВ) значи концентрација на опасни хемиски супстанции во воздухот на работното место внатре во зона на дишење, на која работникот без опасност по здравјето може да е изложен на покусо време. Изложеноста на краткотрајни вредности може да трае највеќе 15 минути и не смее да се повтори повеќе од четирипати во работната смена, при што меѓу две изложености на оваа концентрација мора да измине најмалку 60 минути. Краткотрајната вредност е изразена во mg/m ³ или во ml/m ³ (ppm) а е дадена како многукратни дозволени пречекорувања на граничната вредност; (K) својство на полесно пренесување на супстанците во организмот преку кожата; (EU) European Union – гранична вредност, определена на ниво на Европската унија
Regulatory reference	Правилник за минималните барања за безбедност и здравје при работа на вработени од ризици поврзани со изложување на хемиски супстанции („Службен весник на Република Македонија“ бр.46/10)
Switzerland - Occupational Exposure Limits	
Local name	Ethylèneglycol / Ethylenglykol
MAK (OEL TWA)	26 mg/m ³ 10 ppm
KZGW (OEL STEL)	52 mg/m ³ 20 ppm
Critical toxicity	VRS, Yeux / OAW, Auge
Notation	R, SS _C / H, SS _C
Regulatory reference	www.suva.ch, 01.01.2021

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

Personal protective equipment:

Wear recommended personal protective equipment.

Personal protective equipment symbol(s):



Red Antifreeze

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

8.2.2.1. Eye and face protection

Eye protection:

Safety glasses

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing

Hand protection:

Protective gloves

8.2.2.3. Respiratory protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: red.
Odour	: Not available
Odour threshold	: Not available
Melting point	: Not applicable
Freezing point	: Not available
Boiling point	: Not available
Flammability	: Non flammable.
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: Not available
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: Not available
Viscosity, kinematic	: Not available
Solubility	: Not available
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not available
Vapour pressure at 50 °C	: Not available
Density	: Not available
Relative density	: 1.06 - 1.14
Relative vapour density at 20 °C	: Not available
Particle characteristics	: Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

No additional information available

Red Antifreeze

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Harmful if swallowed.
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Red Antifreeze	
ATE CLP (oral)	1373.626 mg/kg bodyweight
ETHYLENE GLYCOL (107-21-1)	
LD50 oral rat	7712 mg/kg bodyweight Animal: rat
2-ETHYLHEXANOIC ACID, SODIUM SALT (19766-89-3)	
LD50 oral rat	2043 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 401 (Acute Oral Toxicity), 95% CL: 1445 - 2890
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
ETHYLENE GLYCOL (107-21-1)	
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
2-ETHYLHEXANOIC ACID, SODIUM SALT (19766-89-3)	
NOAEL (oral, rat, 90 days)	≈ 300 mg/kg bodyweight Animal: rat, Guideline: EPA OTS 795.2600 (Subchronic Oral Toxicity Test)
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.

Red Antifreeze

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Aspiration hazard : Not classified

11.2. Information on other hazards

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.

Hazardous to the aquatic environment, short-term (acute) : Not classified

Hazardous to the aquatic environment, long-term (chronic) : Not classified

ETHYLENE GLYCOL (107-21-1)

LC50 - Fish [1]	> 72860 mg/l Test organisms (species): Pimephales promelas
EC50 - Crustacea [1]	> 100 mg/l Test organisms (species): Daphnia magna
NOEC (chronic)	≥ 1000 mg/l Test organisms (species): Americamysis bahia (previous name: Mysidopsis bahia) Duration: '23 d'

2-ETHYLHEXANOIC ACID, SODIUM SALT (19766-89-3)

LC50 - Fish [1]	> 100 mg/l Test organisms (species): Oryzias latipes
EC50 - Crustacea [1]	910 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	49.3 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
LOEC (chronic)	63 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	25 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

12.2. Persistence and degradability

Red Antifreeze

Persistence and degradability : Not rapidly degradable

ETHYLENE GLYCOL (107-21-1)

Persistence and degradability : Not rapidly degradable

2-ETHYLHEXANOIC ACID, SODIUM SALT (19766-89-3)

Persistence and degradability : Not rapidly degradable

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

No additional information available

Red Antifreeze

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

12.7. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional legislation (waste)	: Disposal must be done according to official regulations.
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations	: Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	: Disposal must be done according to official regulations.
Additional information	: Do not re-use empty containers.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID number				
Not regulated for transport				
14.2. UN proper shipping name				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.3. Transport hazard class(es)				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.4. Packing group				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.5. Environmental hazards				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
No supplementary information available				

14.6. Special precautions for user

Overland transport

Not regulated

Transport by sea

Not regulated

Air transport

Not regulated

Inland waterway transport

Not regulated

Rail transport

Not regulated

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

Red Antifreeze

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

Contains no REACH substances with Annex XVII restrictions

REACH Annex XIV (Authorisation List)

Contains no REACH Annex XIV substances

REACH Candidate List (SVHC)

Contains no substance on the REACH candidate list

PIC Regulation (Prior Informed Consent)

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

POP Regulation (Persistent Organic Pollutants)

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

Ozone Regulation (1005/2009)

Contains no substance subject to REGULATION (EU) No 1005/2009 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 September 2009 on substances that deplete the ozone layer.

Dual-Use Regulation (428/2009)

Contains no substance subject to the COUNCIL REGULATION (EC) No 428/2009 of 5 May 2009 setting up a Community regime for the control of exports, transfer, brokering and transit of dual-use items.

Explosives Precursors Regulation (2019/1148)

Contains no substance subject to Regulation (EU) 2019/1148 of the European Parliament and of the Council of 20 June 2019 on the marketing and use of explosives precursors.

Drug Precursors Regulation (273/2004)

Contains no substance subject to Regulation (EC) 273/2004 of the European Parliament and of the Council of 11 February 2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances.

15.1.2. National regulations

France

Occupational diseases	
Code	Description
RG 84	Conditions caused by liquid organic solvents for professional use: saturated or unsaturated aliphatic or cyclic liquid hydrocarbons and mixtures thereof; liquid halogenated hydrocarbons; nitrated derivatives of aliphatic hydrocarbons; alcohols; glycols, glycol ethers; ketones; aldehydes; aliphatic and cyclic ethers, including tetrahydrofuran; esters; dimethylformamide and dimethylacetamine; acetonitrile and propionitrile; pyridine; dimethylsulfone and dimethylsulfoxide

Germany

- Employment restrictions : Observe restrictions according Act on the Protection of Working Mothers (MuSchG).
Observe restrictions according Act on the Protection of Young People in Employment (JArbSchG).
- Water hazard class (WGK) : WGK 3, Highly hazardous to water (Classification according to AwSV, Annex 1).
- Hazardous Incident Ordinance (12. BImSchV) : Is not subject of the Hazardous Incident Ordinance (12. BImSchV)

Netherlands

- SZW-lijst van kankerverwekkende stoffen : None of the components are listed
- SZW-lijst van mutagene stoffen : None of the components are listed
- SZW-lijst van reprotoxische stoffen – Borstvoeding : None of the components are listed
- SZW-lijst van reprotoxische stoffen – Vruchtbaarheid : None of the components are listed

Red Antifreeze

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SZW-lijst van reprotoxische stoffen – Ontwikkeling : None of the components are listed

Denmark

Danish National Regulations : Pregnant/breastfeeding women working with the product must not be in direct contact with the product

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Abbreviations and acronyms:	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds

Red Antifreeze

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Abbreviations and acronyms:

CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disrupting properties

Full text of H- and EUH-statements:

Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
H302	Harmful if swallowed.
H373	May cause damage to organs through prolonged or repeated exposure.
STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.