

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
Product name : Graffiti Remover  
Product code : VC3275

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1. Relevant identified uses

Intended for general public  
Main use category : Industrial use, Professional use, Consumer use  
Use of the substance/mixture : Cleaning/washing agents and additives

##### 1.2.2. Uses advised against

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

Valet-Chem Ltd  
Summit Close  
NG17 8GJ Kirkby In Ashfield Nottingham, Nottinghamshire  
United Kingdom  
T +44 (0) 844 414 0987  
[info@valetchem.co.uk](mailto:info@valetchem.co.uk)

#### 1.4. Emergency telephone number

Emergency number : +44 (0) 844 414 0987

Country/Area	Organisation/Company	Address	Emergency number	Comment
United Kingdom	National Poisons Information Service (Birmingham Centre) City Hospital	Dudley Road B18 7QH	0344 892 0111	Only for healthcare professionals
United Kingdom	National Poisons Information Service (Cardiff Centre) University Hospital Llandough	Penlan Road CF64 2XX	0344 892 0111	Only for healthcare professionals
United Kingdom	Guy's & St Thomas' Poisons Unit Medical Toxicology Unit, Guy's & St Thomas' Hospital Trust	Avonley Road SE14 5ER	+44 20 7188 7188	
United Kingdom	National Poisons Information Service (Newcastle Centre) Regional Drugs and Therapeutics Centre	16/17 Framlington Place Newcastle-upon-Tyne NE2 4AB	0344 892 0111	Only for healthcare professionals
United Kingdom	National Poisons Information Service (Belfast Centre) Royal Victoria Hospital	Grosvenor Road BT12 6BA	0344 892 0111	Only for healthcare professionals

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids, Category 2 H225  
Serious eye damage/eye irritation, Category 2 H319  
Specific target organ toxicity — Single exposure, Category 3, H336  
Narcosis

# Graffiti Remover

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Hazardous to the aquatic environment — Chronic Hazard, H412  
Category 3

Full text of H- and EUH-statements: see section 16


### Adverse physicochemical, human health and environmental effects

Highly flammable liquid and vapour. May cause drowsiness or dizziness. Causes serious eye irritation. Harmful to aquatic life with long lasting effects.

## 2.2. Label elements

### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



Signal word (CLP)

: Danger

Contains

: ACETONE; N-BUTYL ACETATE; 1-METHOXY-2-PROPANOL

Hazard statements (CLP)

: H225 - Highly flammable liquid and vapour.  
H319 - Causes serious eye irritation.  
H336 - May cause drowsiness or dizziness.  
H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements (CLP)

: P102 - Keep out of reach of children.  
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P233 - Keep container tightly closed.  
P241 - Use explosion-proof electrical/ventilating/lighting equipment.  
P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.  
P264 - Wash hands, forearms and face thoroughly after handling.  
P271 - Use only outdoors or in a well-ventilated area.  
P273 - Avoid release to the environment.  
P280 - Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.  
P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water .  
P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P312 - Call a POISON CENTRE or doctor if you feel unwell.  
P337+P313 - If eye irritation persists: Get medical advice/attention.  
P370+P378 - In case of fire: Use media other than water to extinguish.  
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.  
P403+P235 - Store in a well-ventilated place. Keep cool.  
P405 - Store locked up.  
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

## 2.3. Other hazards

Contains no PBT/vPvB substances  $\geq 0.1\%$  assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

# Graffiti Remover

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
ACETONE	CAS-No.: 67-64-1 EC-No.: 200-662-2 EC Index-No.: 606-001-00-8	30-50	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
N-BUTYL ACETATE substance with a Community workplace exposure limit	CAS-No.: 123-86-4 EC-No.: 204-658-1 EC Index-No.: 607-025-00-1	30-50	Flam. Liq. 3, H226 STOT SE 3, H336
1-METHOXY-2-PROPANOL	CAS-No.: 107-98-2 EC-No.: 203-539-1 EC Index-No.: 603-064-00-3 REACH-no: 01-2119457435-35	1-10	Flam. Liq. 3, H226 STOT SE 3, H336
2-BUTOXYETHANOL substance with a Community workplace exposure limit	CAS-No.: 111-76-2 EC-No.: 203-905-0 EC Index-No.: 603-014-00-0 REACH-no: 01-2119475108-36	1-10	Acute Tox. 4 (Inhalation), H332 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Oral), H302 Eye Irrit. 2, H319 Skin Irrit. 2, H315
ALCOHOLS C9-11, ETHOXYLATED	CAS-No.: 68439-46-3 EC-No.: 614-482-0 REACH-no: 01-2119980051-45	1-10	Acute Tox. 4 (Oral), H302 Eye Dam. 1, H318

Full text of H- and EUH-statements: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general	: Call a poison center or a doctor if you feel unwell.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Rinse skin with water/shower. Take off immediately all contaminated clothing.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: May cause drowsiness or dizziness.
Symptoms/effects after inhalation	: Although no appropriate human or animal health effects data are known to exist, this material is expected to be an inhalation hazard.
Symptoms/effects after skin contact	: None under normal conditions.
Symptoms/effects after eye contact	: Eye irritation.
Symptoms/effects after ingestion	: None under normal conditions.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Do not use a heavy water stream.

# Graffiti Remover

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 5.2. Special hazards arising from the substance or mixture

- Fire hazard : Highly flammable liquid and vapour.
- Explosion hazard : No direct explosion hazard.
- Hazardous decomposition products in case of fire : Toxic fumes may be released.

### 5.3. Advice for firefighters

- Firefighting instructions : Fight fire from safe distance and protected location. Do not enter fire area without proper protective equipment, including respiratory protection.
- Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material damage.

#### 6.1.1. For non-emergency personnel

- Protective equipment : Wear recommended personal protective equipment.
- Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.

#### 6.1.2. For emergency responders

- Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
- Emergency procedures : Evacuate unnecessary personnel. Stop leak if safe to do so.

### 6.2. Environmental precautions

Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

- For containment : Absorb spilled material with sand or earth. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak without risks if possible.
- Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.
- Other information : Dispose of materials or solid residues at an authorized site.

### 6.4. Reference to other sections

For further information refer to section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

- Additional hazards when processed : Not expected to present a significant hazard under anticipated conditions of normal use.
- Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Use only outdoors or in a well-ventilated area. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.
- Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Ground/bond container and receiving equipment.
- Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.
- Packaging materials : Store always product in container of same material as original container.

# Graffiti Remover

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### Switzerland

Storage class (LK) : LK 3 - Flammable liquids

### 7.3. Specific end use(s)

No additional information available

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### 8.1.1 National occupational exposure and biological limit values

N-BUTYL ACETATE (123-86-4)	
<b>EU - Indicative Occupational Exposure Limit (IOEL)</b>	
Local name	n-Butyl acetate
IOEL TWA	50 ppm
IOEL STEL	723 mg/m <sup>3</sup>
	150 ppm
Regulatory reference	COMMISSION DIRECTIVE (EU) 2019/1831
<b>Austria - Occupational Exposure Limits</b>	
Local name	Butylacetat (Essigsäurebutylester) alle Isomeren außer tert-Butylacetat: n-Butylacetat
MAK (OEL TWA)	241 mg/m <sup>3</sup>
	50 ppm
OEL C	480 mg/m <sup>3</sup>
	100 ppm
Regulatory reference	BGBl. II Nr. 156/2021
<b>Belgium - Occupational Exposure Limits</b>	
Local name	Acétate de n-butyle # n-Butylacetaat
OEL TWA	238 mg/m <sup>3</sup>
	50 ppm
OEL STEL	712 mg/m <sup>3</sup>
	150 ppm
Regulatory reference	Koninklijk besluit/Arrêté royal 19/11/2020
<b>Czech Republic - Occupational Exposure Limits</b>	
Local name	Butylacetát isomery: n-Butyl-acetát
PEL (OEL TWA)	241 mg/m <sup>3</sup>
NPK-P (OEL C)	723 mg/m <sup>3</sup>
Regulatory reference	Nařízení vlády č. 361/2007 Sb. (Předpis 195/2021 Sb.)
<b>Denmark - Occupational Exposure Limits</b>	
Local name	Butylacetat, alle isomere: n-Butylacetat
OEL TWA	241 mg/m <sup>3</sup>
	50 ppm
Remark	E (betyder, at stoffet har en EF-grænseværdi)

# Graffiti Remover

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

<b>N-BUTYL ACETATE (123-86-4)</b>	
Regulatory reference	BEK nr 1426 af 28. juni 2021
<b>Finland - Occupational Exposure Limits</b>	
Local name	n-Butyylisetaatti
HTP (OEL TWA)	240 mg/m <sup>3</sup>
	50 ppm
HTP (OEL STEL)	725 mg/m <sup>3</sup>
	150 ppm
Regulatory reference	HTP-ARVOT 2020 (Sosiaali- ja terveystieteiden ministeriö)
<b>France - Occupational Exposure Limits</b>	
Local name	Acétate de n-butyle
VME (OEL TWA)	710 mg/m <sup>3</sup>
	150 ppm
VLE (OEL C/STEL)	940 mg/m <sup>3</sup>
	200 ppm
Remark	Valeurs recommandées/admises
Regulatory reference	Circulaire du Ministère du travail (réf.: INRS ED 984, 2016)
<b>Germany - Occupational Exposure Limits (TRGS 900)</b>	
AGW (OEL TWA)	300 mg/m <sup>3</sup>
	62 ppm
Peak exposure limitation factor	2(l)
Remark	AGS - Ausschuss für Gefahrstoffe; Y - Ein Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes (BGW) nicht befürchtet zu werden
Regulatory reference	TRGS900
<b>Greece - Occupational Exposure Limits</b>	
Local name	Οξικός- βουτυλεστέρας, n-
OEL TWA	710 mg/m <sup>3</sup>
	150 ppm
OEL STEL	950 mg/m <sup>3</sup>
	200 ppm
Regulatory reference	Π.Δ. 90/1999 - Προστασία της υγείας των εργαζομένων που εκτίθενται σε ορισμένους χημικούς παράγοντες κατά τη διάρκεια της εργασίας τους
<b>Hungary - Occupational Exposure Limits</b>	
Local name	n-BUTIL-ACETÁT
AK (OEL TWA)	241 mg/m <sup>3</sup>
CK (OEL STEL)	723 mg/m <sup>3</sup>
Remark	i (ingerlő anyag, amely izgatja a bőrt, nyálkahártyát, szemet vagy mindhármát), sz (Túlérzékenységet okozó (szenzibilizáló) tulajdonságú anyag. Az anyagra érzékeny egyéneken „túlérzékenységen” alapuló bőr-, légzőrendszeri, esetleg más szervet/szervrendszert károsító megbetegedést okozhat); N (Irritáló anyagok, egyszerű fojtógázok, csekély egészségkárosító hatással bíró anyagok)

# Graffiti Remover

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

<b>N-BUTYL ACETATE (123-86-4)</b>	
Regulatory reference	5/2020. (II. 6.) ITM rendelet - A kémiai kóroki tényezők hatásának kitett munkavállalók egészségének és biztonságának védelméről
<b>Ireland - Occupational Exposure Limits</b>	
Local name	n-Butyl acetate
OEL TWA	241 mg/m <sup>3</sup>
	50 ppm
OEL STEL	723 mg/m <sup>3</sup>
	150 ppm
Remark	IOELV (Indicative Occupational Exposure Limit Values)
Regulatory reference	Chemical Agents Code of Practice 2021
<b>Italy - Occupational Exposure Limits</b>	
Local name	Acetato di n-butile
OEL TWA	241 mg/m <sup>3</sup>
	50 ppm
OEL STEL	723 mg/m <sup>3</sup>
	150 ppm
Regulatory reference	Allegato XXXVIII del D.Lgs. 9 aprile 2008, n. 81 e s.m.i.
<b>Latvia - Occupational Exposure Limits</b>	
Local name	Etiķskābes butilesteris (n-butilacetāts)
OEL TWA	241 mg/m <sup>3</sup>
	50 ppm
OEL STEL	723 mg/m <sup>3</sup>
	150 ppm
Regulatory reference	Ministru kabineta 2007. gada 15. maija noteikumiem Nr. 325 (Grozījumi Ministru kabineta 2021. gada 18. februārī noteikumiem Nr. 110)
<b>Spain - Occupational Exposure Limits</b>	
Local name	Acetato de n-butilo
VLA-ED (OEL TWA)	241 mg/m <sup>3</sup>
	50 ppm
VLA-EC (OEL STEL)	724 mg/m <sup>3</sup>
	150 ppm
Remark	VLI (Agente químico para el que la U.E. estableció en su día un valor límite indicativo).
Regulatory reference	Límites de Exposición Profesional para Agentes Químicos en España 2021. INSHT
<b>Sweden - Occupational Exposure Limits</b>	
Local name	n-Butylacetat
NGV (OEL TWA)	241 mg/m <sup>3</sup>
	50 ppm
KTV (OEL STEL)	723 mg/m <sup>3</sup>
	150 ppm
Regulatory reference	Hygieniska gränsvärden (AFS 2020:6)

# Graffiti Remover

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

<b>N-BUTYL ACETATE (123-86-4)</b>	
<b>United Kingdom - Occupational Exposure Limits</b>	
Local name	Butyl acetate
WEL TWA (OEL TWA)	724 mg/m <sup>3</sup>
	150 ppm
WEL STEL (OEL STEL)	966 mg/m <sup>3</sup>
	200 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
<b>Iceland - Occupational Exposure Limits</b>	
Local name	Bútylasetat, allir ísómerar (ísóbútylasetat)
OEL TWA	241 mg/m <sup>3</sup>
	50 ppm
OEL STEL	723 mg/m <sup>3</sup>
	150 ppm
Regulatory reference	Reglugerð um mengunarmörk og aðgerðir til að draga úr mengun á vinnustöðum (Nr. 631/2021)
<b>Switzerland - Occupational Exposure Limits</b>	
Local name	1-Butylacétate / 1-Butylacetat [Essigsäurebutylester]
MAK (OEL TWA)	240 mg/m <sup>3</sup>
	50 ppm
KZGW (OEL STEL)	720 mg/m <sup>3</sup>
	150 ppm
Critical toxicity	VR, Yeux / AW, Auge
Notation	SS <sub>c</sub> / SS <sub>c</sub>
Remark	INRS, NIOSH
Regulatory reference	www.suva.ch, 01.01.2021
<b>2-BUTOXYETHANOL (111-76-2)</b>	
<b>EU - Indicative Occupational Exposure Limit (IOEL)</b>	
Local name	2-Butoxyethanol
IOEL TWA	20 ppm
IOEL STEL	246 mg/m <sup>3</sup>
	50 ppm
Remark	Skin
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
<b>Austria - Occupational Exposure Limits</b>	
Local name	2-Butoxyethanol (Butylglykol; Ethylenglykolmonobutylether)
MAK (OEL TWA)	98 mg/m <sup>3</sup>
	20 ppm
MAK (OEL STEL)	200 mg/m <sup>3</sup> (4x 30(Miw) min)
	40 ppm (4x 30(Miw) min)



# Graffiti Remover

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

2-BUTOXYETHANOL (111-76-2)	
Remark	H
Regulatory reference	BGBI. II Nr. 156/2021
<b>Belgium - Occupational Exposure Limits</b>	
Local name	2-Butoxyéthanol # 2-Butoxy-ethanol
OEL TWA	98 mg/m <sup>3</sup>
	20 ppm
OEL STEL	246 mg/m <sup>3</sup>
	50 ppm
Remark	D: la mention "D" signifie que la résorption de l'agent, via la peau, les muqueuses ou les yeux, constitue une partie importante de l'exposition totale. Cette résorption peut se faire tant par contact direct que par présence de l'agent dans l'air. # D: de vermelding "D" betekent dat de opname van het agens via de huid, de slijmvliezen of de ogen een belangrijk deel van de totale blootstelling vormt. Deze opname kan het gevolg zijn van zowel direct contact als zijn aanwezigheid in de lucht.
Regulatory reference	Koninklijk besluit/Arrêté royal 19/11/2020
<b>Bulgaria - Occupational Exposure Limits</b>	
Local name	2-Бутоксиетанол
OEL TWA	98 mg/m <sup>3</sup>
	20 ppm
OEL STEL	246 mg/m <sup>3</sup>
	50 ppm
Remark	Кожа (възможна е значителна резорбция чрез кожата); * (Химични агенти, за които са определени гранични стойности във въздуха на работната среда за Европейската общност)
Regulatory reference	Наредба № 13 от 30.12.2003 г. за защита на работещите от рискове, свързани с експозиция на химични агенти при работа (изм. и доп. ДВ. бр. 47 от 2021 г., в сила от 04.06.2021 г.)
<b>Croatia - Occupational Exposure Limits</b>	
Local name	2-Butoksietanol; etilen-glikol monobutil-eter; butilov celosolv
GVI (OEL TWA)	98 mg/m <sup>3</sup>
	20 ppm
KGVI (OEL STEL)	246 mg/m <sup>3</sup>
	50 ppm
Remark	Direktiva: 2000/39/EZ. Napomena: Koža (razvrstana kao tvar koja nadražuje kožu (H315))
Regulatory reference	Pravilnik o izmjenama i dopunama Pravilnika o graničnim vrijednostima izloženosti opasnim tvarima pri radu i o biološkim graničnim vrijednostima (NN 1/2021)
<b>Cyprus - Occupational Exposure Limits</b>	
Local name	2-Βουτοξυαιθανόλη
OEL TWA	98 mg/m <sup>3</sup>
	20 ppm
OEL STEL	246 mg/m <sup>3</sup>
	50 ppm

# Graffiti Remover

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

<b>2-BUTOXYETHANOL (111-76-2)</b>	
Remark	δέγμα
Regulatory reference	Κανονισμοί του 2007 (Κ.Δ.Π. 295/2007)
<b>Czech Republic - Occupational Exposure Limits</b>	
Local name	2-Butoxyethanol (Butylcellosolv; Ethylenglykolmonobutylether)
PEL (OEL TWA)	100 mg/m <sup>3</sup> 20 ppm
NPK-P (OEL C)	200 mg/m <sup>3</sup> 41 ppm
Remark	D - při expozici se významně uplatňuje pronikání faktoru kůží, I - dráždí sliznice (oči, dýchací cesty), respektive kůži, B - u látky je zaveden biologický expoziční test (BET) v moči nebo krvi.
Regulatory reference	Nařízení vlády č. 361/2007 Sb. (Předpis 195/2021 Sb.)
<b>Czech Republic - Biological limit values</b>	
Local name	2-Butoxyethanol (Butylcellosolv, Ethylenglykolmonobutylether)
BLV	200 mg/g creatinine Ukazatel: Butoxyoctová kyselina - Biološki uzorak: moči - Doba odběru: konec směny na konci 0.17 mmol/mmol Creatinine Ukazatel: Butoxyoctová kyselina - Biološki uzorak: moči - Doba odběru: konec směny na konci
Regulatory reference	Vyhláška č. 107/2013 Sb. (kterou se mění vyhláška č. 432/2003 Sb.)
<b>Denmark - Occupational Exposure Limits</b>	
Local name	Butylglycol (2-Butoxyethanol; Butylcellosolve; Ethylenglykolmonobutylether)
OEL TWA	98 mg/m <sup>3</sup> 20 ppm
Remark	E (betyder, at stoffet har en EF-grænseværdi); H (betyder, at stoffet kan optages gennem huden)
Regulatory reference	BEK nr 1426 af 28. juni 2021
<b>Estonia - Occupational Exposure Limits</b>	
Local name	2-butoksüetanol (o-butüületüleenglükool, etüleenglükoolmono-butüüleeter, butüületsellosolv)
OEL TWA	98 mg/m <sup>3</sup> 20 ppm
OEL STEL	246 mg/m <sup>3</sup> 50 ppm
Remark	A (Naha kaudu kergesti imenduv aine), S (Sensibiliseeriv aine)
Regulatory reference	Vabariigi Valitsuse 20. märtsi 2001. a määruse nr 105 (RT I, 17.10.2019, 2); Vabariigi Valitsuse 10. märtsi 2019. a määruse nr 84
<b>Finland - Occupational Exposure Limits</b>	
Local name	2-Butoksietanoli
HTP (OEL TWA)	98 mg/m <sup>3</sup> 20 ppm
HTP (OEL STEL)	250 mg/m <sup>3</sup> 50 ppm

# Graffiti Remover

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

2-BUTOXYETHANOL (111-76-2)	
Remark	lho
Regulatory reference	HTP-ARVOT 2020 (Sosiaali- ja terveysministeriö)
<b>France - Occupational Exposure Limits</b>	
Local name	2-Butoxyéthanol (Butylglycol)
VME (OEL TWA)	49 mg/m <sup>3</sup> 10 ppm
VLE (OEL C/STEL)	246 mg/m <sup>3</sup> 50 ppm
Remark	Valeurs réglementaires contraignantes; risque de pénétration percutanée
Regulatory reference	Article R4412-149 du Code du travail (réf.: INRS ED 984, 2016; Décret n° 2019-1487; Décret n° 2020-1546; Décret n°2021-434)
<b>Germany - Occupational Exposure Limits (TRGS 900)</b>	
AGW (OEL TWA)	49 mg/m <sup>3</sup> 10 ppm
Peak exposure limitation factor	2(l)
Remark	EU - Europäische Union (Von der EU wurde ein Luftgrenzwert festgelegt: Abweichungen bei Wert und Spitzenbegrenzung sind möglich); DFG - Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe der DFG (MAK-Kommission); H - hautresorptiv; Y - Ein Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes (BGW) nicht befürchtet zu werden
Regulatory reference	TRGS900
<b>Germany - Biological limit values (TRGS 903)</b>	
Local name	2-Butoxyethanol
Biological limit value	150 mg/g creatinine Parameter: Butoxyessigsäure (nach Hydrolyse) - Untersuchungsmaterial: U = Urin - Probenahmezeitpunkt: b) Expositionsende, bzw. Schichtende, c) bei Langzeitexposition: am Schichtende nach mehreren vorangegangenen Schichten - Festlegung/Begründung: 11/2016 DFG
Regulatory reference	TRGS 903
<b>Gibraltar - Occupational Exposure Limits</b>	
Local name	2-Butoxyethanol
OEL TWA	98 mg/m <sup>3</sup> 20 ppm
OEL STEL	246 mg/m <sup>3</sup> 50 ppm
Remark	Skin
Regulatory reference	Factories (Control of Chemical Agents at Work) Regulations 2003 (LN. 2018/181)
<b>Greece - Occupational Exposure Limits</b>	
Local name	Βουτοξυ-αιθανόλη, 2-
OEL TWA	120 mg/m <sup>3</sup> 25 ppm
Remark	Η ένδειξη «δέρμα» στις οριακές τιμές επαγγελματικής έκθεσης επισημαίνει το ενδεχόμενο σημαντικής διείσδυσης μέσω του δέρματος.

# Graffiti Remover

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

2-BUTOXYETHANOL (111-76-2)	
Regulatory reference	Π.Δ. 90/1999 - Προστασία της υγείας των εργαζομένων που εκτίθενται σε ορισμένους χημικούς παράγοντες κατά τη διάρκεια της εργασίας τους
<b>Hungary - Occupational Exposure Limits</b>	
Local name	2-BUTOXIETANOL
AK (OEL TWA)	98 mg/m <sup>3</sup>
CK (OEL STEL)	246 mg/m <sup>3</sup>
Remark	b (Bőrön át is felszívódik), i (ingerlő anyag, amely izgatja a bőrt, nyálkahártyát, szemet vagy mindhármát); EU1 (2000/39/EK irányelvben közölt érték); T (Azok az anyagok, amelyek egészségkárosító hatása TARTÓS expozíciót követően jelentkezik)
Regulatory reference	5/2020. (II. 6.) ITM rendelet - A kémiai kóroki tényezők hatásának kitett munkavállalók egészségének és biztonságának védelméről
<b>Ireland - Occupational Exposure Limits</b>	
Local name	2-Butoxyethanol (EGBE) [Ethylene glycol monobutyl ether]
OEL TWA	98 mg/m <sup>3</sup> 20 ppm
OEL STEL	246 mg/m <sup>3</sup> 50 ppm
Remark	Sk (Substances which have the capacity to penetrate intact skin when they come in contact with it, and be absorbed into the body), IOELV (Indicative Occupational Exposure Limit Values)
Regulatory reference	Chemical Agents Code of Practice 2021
<b>Ireland - Biological limit values</b>	
Local name	2-Butoxyethanol
BMGV	200 mg/g creatinine Parameter: BAA - Medium: urine - Sampling time: End of shift
Regulatory reference	Biological Monitoring Guidelines (HSA, 2011)
<b>Italy - Occupational Exposure Limits</b>	
Local name	Butossietanolo-2
OEL TWA	98 mg/m <sup>3</sup> 20 ppm
OEL STEL	246 mg/m <sup>3</sup> 50 ppm
Remark	Cute
Regulatory reference	Allegato XXXVIII del D.Lgs. 9 aprile 2008, n. 81 e s.m.i.
<b>Latvia - Occupational Exposure Limits</b>	
Local name	2-Butoksietanols, (etilēnglikola monobutilēteris, Butilcelosolvs)
OEL TWA	98 mg/m <sup>3</sup> 20 ppm
OEL STEL	246 mg/m <sup>3</sup> 50 ppm
Remark	Āda
Regulatory reference	Ministru kabineta 2007. gada 15. maija noteikumiem Nr. 325

# Graffiti Remover

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

<b>2-BUTOXYETHANOL (111-76-2)</b>	
<b>Lithuania - Occupational Exposure Limits</b>	
Local name	Etilenglikolio monobutyleteris (butilglikolis, 2-butoksietanolis)
IPRV (OEL TWA)	50 mg/m <sup>3</sup>
	10 ppm
TPRV (OEL STEL)	100 mg/m <sup>3</sup>
	20 ppm
Remark	O (medžiaga į organizmą gali prasiskverbti pro nepažeistą odą)
Regulatory reference	LIETUVOS HIGIENOS NORMA HN 23:2011 (Nr. V-695/A1-272, 2018-06-12)
<b>Luxembourg - Occupational Exposure Limits</b>	
Local name	2-Butoxyéthanol
OEL TWA	98 mg/m <sup>3</sup>
	20 ppm
OEL STEL	246 mg/m <sup>3</sup>
	50 ppm
Remark	Peau
Regulatory reference	Mémorial A N° 226 de 2021 concernant la protection de la sécurité et de la santé des salariés contre les risques liés à des agents chimiques sur le lieu de travail
<b>Malta - Occupational Exposure Limits</b>	
Local name	2-Butoxyethanol
OEL TWA	98 mg/m <sup>3</sup>
	20 ppm
OEL STEL	246 mg/m <sup>3</sup>
	50 ppm
Remark	Skin # Ġilda
Regulatory reference	S.L.424.24 - Chemical Agents at Work Regulations (L.N.57 of 2018)
<b>Netherlands - Occupational Exposure Limits</b>	
Local name	2-Butoxyethanol
TGG-8u (OEL TWA)	100 mg/m <sup>3</sup>
TGG-15min (OEL STEL)	246 mg/m <sup>3</sup>
Remark	H (Huidopname) Stoffen die relatief gemakkelijk door de huid kunnen worden opgenomen, hetgeen een substantiële bijdrage kan betekenen aan de totale inwendige blootstelling, hebben in de lijst een H-aanduiding. Bij deze stoffen moeten naast maatregelen tegen inademing ook adequate maatregelen ter voorkoming van huidcontact worden genomen.
Regulatory reference	Arbeidsomstandighedenregeling 2021
<b>Poland - Occupational Exposure Limits</b>	
Local name	2-Butoksyetanol (butoksyetylowy alkohol)
NDS (OEL TWA)	98 mg/m <sup>3</sup>
NDSCh (OEL STEL)	200 mg/m <sup>3</sup>
Remark	Skóra (Oznakowanie substancji notacją „skóra” oznacza, że wchłanianie substancji przez skórę może być tak samo istotne jak przy narażeniu drogą oddechową).
Regulatory reference	Dz. U. 2018 poz. 1286

# Graffiti Remover

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

2-BUTOXYETHANOL (111-76-2)	
<b>Portugal - Occupational Exposure Limits</b>	
Local name	2-Butoxietanol (EGBE)
OEL TWA	20 ppm
Remark	A3 (Agente carcinogénico confirmado nos animais de laboratório com relevância desconhecida no Homem); IBE (Índice biológico de exposição)
Regulatory reference	Norma Portuguesa NP 1796:2014
<b>Portugal - Biological Exposure Indices</b>	
Local name	2-Butoxietanol (EGBE)
BEI	200 mg/g creatinine Parâmetro: Ácido butoxiacético (BAA) - Meio: urina - Momento da amostragem: Fim do turno - Notação: Com hidrólise
Regulatory reference	Norma Portuguesa NP 1796:2014
<b>Romania - Occupational Exposure Limits</b>	
Local name	2-Butoxietanol/Etilenglicol monobutileter
OEL TWA	98 mg/m <sup>3</sup> 20 ppm
OEL STEL	246 mg/m <sup>3</sup> 50 ppm
Remark	P - posibilitatea unei penetrări cutanate importante
Regulatory reference	Hotărârea Guvernului nr. 1.218/2006 (Hotărârea nr. 53/2021)
<b>Serbia - Occupational Exposure Limits</b>	
Local name	2-бутоксietанол
OEL TWA	98 mg/m <sup>3</sup> 20 ppm
OEL STEL	246 mg/m <sup>3</sup> 50 ppm
Remark	EU* – напомена да се ради о хемијским материјама за које су утврђене индикативне граничне вредности изложености према Директиви 2000/39/ЕЗ (прва листа)
Regulatory reference	ПРАВИЛНИК о превентивним мерама за безбедан и здрав рад при излагању хемијским материјама („Службени гласник РС”, бр. 106/09 и 117/17)
<b>Slovakia - Occupational Exposure Limits</b>	
Local name	2-Butoxyetanol (butylglykol)
NPHV (OEL TWA)	98 mg/m <sup>3</sup> 20 ppm
NPHV (OEL STEL)	246 mg/m <sup>3</sup> 50 ppm
Remark	K - znamená, že faktor môže byť ľahko absorbovaný kožou
Regulatory reference	Nariadenie vlády č. 355/2006 Z. z. (236/2020 Z. z.)
<b>Slovenia - Occupational Exposure Limits</b>	
Local name	2-butoksietanol (butilglikol)
OEL TWA	98 mg/m <sup>3</sup>

# Graffiti Remover

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

2-BUTOXYETHANOL (111-76-2)	
	20 ppm
OEL STEL	246 mg/m <sup>3</sup>
	50 ppm
Remark	K (Lastnost lažjega prehajanja snovi v organizem skozi kožo), Y (Snovi, pri katerih ni nevarnosti za zarodek ob upoštevanju mejnih vrednosti in bat vrednosti), BAT (Biološka mejna vrednost), EU
Regulatory reference	Uradni list RS, št. 72/2021 z dne 11.5.2021
Slovenia - Biological limit values	
Local name	2-butoksietanol
BLV	150 mg/g creatinine Parameter: butoksiocetna kislina (po hidrolizi) - Biološki vzorec: urin - Čas vzorčenja: ob koncu delovne izmene, pri dolgotrajni izpostavljenosti: ob koncu delovne izmene po več zaporednih delavnikih
Regulatory reference	Uradni list RS, št. 72/2021 z dne 11.5.2021
Spain - Occupational Exposure Limits	
Local name	2-Butoxietanol (Butil cellosolve; Éter monobutílico del etilenglicol)
VLA-ED (OEL TWA)	98 mg/m <sup>3</sup>
	20 ppm
VLA-EC (OEL STEL)	245 mg/m <sup>3</sup>
	50 ppm
Remark	Vía dérmica (Indica que, en las exposiciones a esta sustancia, la aportación por la vía cutánea puede resultar significativa para el contenido corporal total si no se adoptan medidas para prevenir la absorción. En estas situaciones, es aconsejable la utilización del control biológico para poder cuantificar la cantidad global absorbida del contaminante), VLI (Agente químico para el que la U.E. estableció en su día un valor límite indicativo), VLB® (Agente químico que tiene Valor Límite Biológico).
Regulatory reference	Límites de Exposición Profesional para Agentes Químicos en España 2021. INSHT
Spain - Biological limit values	
Local name	2-Butoxietanol (Butil cellosolve; Éter monobutílico del etilenglicol)
BLV	200 mg/g creatinine Parámetro: Ácido butoxiacético - Medio: Orina - Momento de muestreo: Final de la jornada laboral - Notas: Con hidrólisis
Regulatory reference	Límites de Exposición Profesional para Agentes Químicos en España 2021. INSHT
Sweden - Occupational Exposure Limits	
Local name	Etylenglykolmonobutyleter (2-Butoxietanol)
NGV (OEL TWA)	50 mg/m <sup>3</sup>
	10 ppm
KTV (OEL STEL)	246 mg/m <sup>3</sup>
	50 ppm
Remark	H (Ämnet kan lätt upptas genom huden. Det föreskrivna gränsvärdet bedöms ge tillräckligt skydd endast under förutsättning att huden är skyddad mot exponering för ämnet ifråga)
Regulatory reference	Hygieniska gränsvärden (AFS 2018:1)
United Kingdom - Occupational Exposure Limits	
Local name	2-Butoxyethanol
WEL TWA (OEL TWA)	123 mg/m <sup>3</sup>

# Graffiti Remover

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

2-BUTOXYETHANOL (111-76-2)	
	25 ppm
WEL STEL (OEL STEL)	246 mg/m <sup>3</sup>
	50 ppm
Remark	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
United Kingdom - Biological limit values	
Local name	2-Butoxyethanol
BMGV	240 mmol/mol Creatinine Parameter: butoxyacetic acid - Medium: urine - Sampling time: Post shift
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
Iceland - Occupational Exposure Limits	
Local name	2-Bútoxýetanól (bútýlglykól, bútýlsellósov, etýlenglykólmonóbútýleter, glykólmonóbútýleter)
OEL TWA	100 mg/m <sup>3</sup>
	20 ppm
OEL STEL	246 mg/m <sup>3</sup>
	50 ppm
Remark	H (efnið getur auðveldlega borist inn í líkamann gegnum húð)
Regulatory reference	Reglugerð um mengunarmörk og aðgerðir til að draga úr mengun á vinnustöðum (Nr. 390/2009)
Norway - Occupational Exposure Limits	
Local name	2-butoksyetanol (Butylglykol; Etylenglykolmonobutyleter)
Grenseverdi (OEL TWA)	50 mg/m <sup>3</sup>
	10 ppm
Remark	H: Kjemikalier som kan tas opp gjennom huden; E: EU har en veiledende grenseverdi og/eller anmerkning for stoffet.
Regulatory reference	FOR-2021-06-28-2248
North Macedonia - Occupational Exposure Limits	
Local name	2-бутоксietанол (бутилгликол)
OEL TWA	98 mg/m <sup>3</sup>
	20 ppm
KTV	2.5
Short time value [mg/m <sup>3</sup> ]	245 mg/m <sup>3</sup>
Short time value [ppm]	50 ppm



# Graffiti Remover

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

2-BUTOXYETHANOL (111-76-2)	
Remark	(KTV) краткотрајна вредност (КТВ) значи концентрација на опасни хемиски супстанции во воздухот на работното место внатре во зона на дишење, на која работникот без опасност по здравјето може да е изложен на покусо време. Изложеноста на краткотрајни вредности може да трае највеќе 15 минути и не смее да се повтори повеќе од четирипати во работната смена, при што меѓу две изложености на оваа концентрација мора да измине најмалку 60 минути. Краткотрајната вредност е изразена во mg/m <sup>3</sup> или во ml/m <sup>3</sup> (ppm) а е дадена како многукратни дозволени пречекорувања на граничната вредност; (К) својство на полесно пренесување на супстанците во организмот преку кожата; (EU) European Union – гранична вредност, определена на ниво на Европската унија
Regulatory reference	Правилник за минималните барања за безбедност и здравје при работа на вработени од ризици поврзани со изложување на хемиски супстанции („Службен весник на Република Македонија“ бр.46/10)
Switzerland - Occupational Exposure Limits	
Local name	2-Butoxyéthanol / 2-Butoxyethanol [Butylglykol, Ethylenglykolmonobutylether]
MAK (OEL TWA)	49 mg/m <sup>3</sup> 10 ppm
KZGW (OEL STEL)	98 mg/m <sup>3</sup> 20 ppm
Critical toxicity	VRS, Yeux / OAW, Auge
Notation	R, SS <sub>C</sub> , B / H, SS <sub>C</sub> , B
Remark	INRS, HSE, NIOSH
Regulatory reference	www.suva.ch, 01.01.2021
Switzerland - BAT	
Local name	2-Butoxyéthanol / 2-Butoxyethanol
BAT	150 mg/g creatinine (Paramètre biologique: Acide 2-butoxyacétique (après hydrolyse); Substrat d'examen: Urine; Moment du prélèvement: Fin de l'exposition, de la période de travail. Exposition de longue durée: après plusieurs périodes de travail.) / (Biologischer Parameter: 2-Butoxyessigsäure (nach Hydrolyse); Untersuchungsmaterial: Urin; Probenahmezeitpunkt: Expositionsende, bzw. Schichtende. Bei Langzeitexposition: nach mehreren vorangegangenen Schichten.)
Regulatory reference	Ordonnance 832.30 (OPA), article 50 al. 3, www.suva.ch/valeurs-limites / Verordnung 832.30 (VUV), Art. 50 Abs. 3, www.suva.ch/grenzwerte

### 8.1.2. Recommended monitoring procedures

No additional information available

### 8.1.3. Air contaminants formed

No additional information available

### 8.1.4. DNEL and PNEC

No additional information available

### 8.1.5. Control banding

No additional information available

## 8.2. Exposure controls

### 8.2.1. Appropriate engineering controls

#### Appropriate engineering controls:

Ensure good ventilation of the work station.

# Graffiti Remover

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 8.2.2. Personal protection equipment

#### Personal protective equipment:

Gloves. Safety glasses. Protective clothing.

#### Personal protective equipment symbol(s):



#### 8.2.2.1. Eye and face protection

##### Eye protection:

Safety glasses

#### 8.2.2.2. Skin protection

##### Skin and body protection:

Wear suitable protective clothing

##### Hand protection:

Protective gloves

#### 8.2.2.3. Respiratory protection

##### Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

#### 8.2.2.4. Thermal hazards

No additional information available

### 8.2.3. Environmental exposure controls

#### Environmental exposure controls:

Avoid release to the environment.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Not available
Odour	: Not available
Odour threshold	: Not available
Melting point	: Not applicable
Freezing point	: Not available
Boiling point	: ≈ 79 °C
Flammability	: Highly flammable liquid and vapour.
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: ≈ -4 °C
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: Not available
Viscosity, kinematic	: Not available
Solubility	: Not available
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not available
Vapour pressure at 50 °C	: Not available
Density	: Not available
Relative density	: Not available
Relative vapour density at 20 °C	: Not available
Particle characteristics	: Not applicable

# Graffiti Remover

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 9.2. Other information

#### 9.2.1. Information with regard to physical hazard classes

No additional information available

#### 9.2.2. Other safety characteristics

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Highly flammable liquid and vapour.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified  
Acute toxicity (dermal) : Not classified  
Acute toxicity (inhalation) : Not classified

1-METHOXY-2-PROPANOL (107-98-2)	
LD50 oral	11700 mg/kg
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: EU Method B.3 (Acute Toxicity (Dermal))
2-BUTOXYETHANOL (111-76-2)	
LD50 oral rat	1746 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 401 (Acute Oral Toxicity), 95% CL: 1322 - 2301
LD50 oral	1414 mg/kg bodyweight Animal: guinea pig, Guideline: OECD Guideline 401 (Acute Oral Toxicity), 95% CL: 1020 - 1961
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
ALCOHOLS C9-11, ETHOXYLATED (68439-46-3)	
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LC50 Inhalation - Rat	> 1.6 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity), Remarks on results: other:

Skin corrosion/irritation : Not classified

# Graffiti Remover

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: May cause drowsiness or dizziness.

### ACETONE (67-64-1)

STOT-single exposure	May cause drowsiness or dizziness.
----------------------	------------------------------------

### N-BUTYL ACETATE (123-86-4)

STOT-single exposure	May cause drowsiness or dizziness.
----------------------	------------------------------------

### 1-METHOXY-2-PROPANOL (107-98-2)

STOT-single exposure	May cause drowsiness or dizziness.
----------------------	------------------------------------

STOT-repeated exposure	: Not classified
------------------------	------------------

### 1-METHOXY-2-PROPANOL (107-98-2)

LOAEL (oral, rat, 90 days)	2757 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents)
----------------------------	--

NOAEL (oral, rat, 90 days)	919 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents)
----------------------------	---

NOAEL (dermal, rat/rabbit, 90 days)	> 1000 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study)
-------------------------------------	--

### 2-BUTOXYETHANOL (111-76-2)

NOAEL (dermal, rat/rabbit, 90 days)	> 150 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 411 (Subchronic Dermal Toxicity: 90-Day Study), Remarks on results: other:
-------------------------------------	---

### ALCOHOLS C9-11, ETHOXYLATED (68439-46-3)

NOAEL (oral, rat, 90 days)	≥ 500 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
----------------------------	---

Aspiration hazard	: Not classified
-------------------	------------------

### 1-METHOXY-2-PROPANOL (107-98-2)

Viscosity, kinematic	1.848 mm <sup>2</sup> /s
----------------------	--------------------------

## 11.2. Information on other hazards

No additional information available

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general	: Harmful to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Harmful to aquatic life with long lasting effects.

### N-BUTYL ACETATE (123-86-4)

EC50 - Other aquatic organisms [1]	32 mg/l Test organisms (species): Artemia salina
------------------------------------	--

EC50 72h - Algae [1]	674.7 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
----------------------	---

# Graffiti Remover

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

<b>1-METHOXY-2-PROPANOL (107-98-2)</b>	
EC50 - Other aquatic organisms [1]	2954 mg/l Test organisms (species): other aquatic crustacea:
<b>2-BUTOXYETHANOL (111-76-2)</b>	
LC50 - Fish [1]	1474 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 - Crustacea [1]	≈ 1800 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	911 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 72h - Algae [2]	1840 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
NOEC (chronic)	100 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	≥ 100 mg/l Test organisms (species): Oryzias latipes Duration: '14 d'
<b>ALCOHOLS C9-11, ETHOXYLATED (68439-46-3)</b>	
LC50 - Fish [1]	5 – 7 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 - Crustacea [1]	2.5 mg/l Test organisms (species): Daphnia magna
EC50 96h - Algae [1]	1.4 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)

### 12.2. Persistence and degradability

<b>Graffiti Remover</b>	
Persistence and degradability	Not rapidly degradable
<b>ACETONE (67-64-1)</b>	
Persistence and degradability	Not rapidly degradable
<b>N-BUTYL ACETATE (123-86-4)</b>	
Persistence and degradability	Not rapidly degradable
<b>1-METHOXY-2-PROPANOL (107-98-2)</b>	
Persistence and degradability	Not rapidly degradable
<b>2-BUTOXYETHANOL (111-76-2)</b>	
Persistence and degradability	Not rapidly degradable
<b>ALCOHOLS C9-11, ETHOXYLATED (68439-46-3)</b>	
Persistence and degradability	Not rapidly degradable

### 12.3. Bioaccumulative potential

No additional information available

### 12.4. Mobility in soil

No additional information available

### 12.5. Results of PBT and vPvB assessment

No additional information available

### 12.6. Endocrine disrupting properties

No additional information available

# Graffiti Remover

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 12.7. Other adverse effects

No additional information available






## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Regional legislation (waste)	: Disposal must be done according to official regulations.
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations	: Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	: Disposal must be done according to official regulations.
Additional information	: Flammable vapours may accumulate in the container. Do not re-use empty containers.

## SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
<b>14.1. UN number or ID number</b>				
UN 1090	UN 1090	UN 1090	UN 1090	UN 1090
<b>14.2. UN proper shipping name</b>				
ACETONE	ACETONE	Acetone	ACETONE	ACETONE
<b>Transport document description</b>				
UN 1090 ACETONE, 3, II, (D/E)	UN 1090 ACETONE, 3, II (-20°C c.c.)	UN 1090 Acetone, 3, II	UN 1090 ACETONE, 3, II	UN 1090 ACETONE, 3, II
<b>14.3. Transport hazard class(es)</b>				
3	3	3	3	3
				
<b>14.4. Packing group</b>				
II	II	II	II	II
<b>14.5. Environmental hazards</b>				
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No
No supplementary information available				

### 14.6. Special precautions for user

#### Overland transport


Classification code (ADR)	: F1
Limited quantities (ADR)	: 1I
Excepted quantities (ADR)	: E2
Packing instructions (ADR)	: P001, IBC02, R001
Mixed packing provisions (ADR)	: MP19
Portable tank and bulk container instructions (ADR)	: T4
Portable tank and bulk container special provisions (ADR)	: TP1
Tank code (ADR)	: LGBF
Vehicle for tank carriage	: FL

# Graffiti Remover

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Transport category (ADR) : 2  
Special provisions for carriage - Operation (ADR) : S2, S20  
Hazard identification number (Kemler No.) : 33  
Orange plates :



Tunnel restriction code (ADR) : D/E  
EAC code : •2YE

### Transport by sea

Limited quantities (IMDG) : 1 L  
Excepted quantities (IMDG) : E2  
Packing instructions (IMDG) : P001  
IBC packing instructions (IMDG) : IBC02  
Tank instructions (IMDG) : T4  
Tank special provisions (IMDG) : TP1  
EmS-No. (Fire) : F-E  
EmS-No. (Spillage) : S-D  
Stowage category (IMDG) : E  
Flash point (IMDG) : -20°C to -18°C c.c.  
Properties and observations (IMDG) : Colourless, clear liquid, with a characteristic mint-like odour. Flashpoint: -20°C to -18°C c.c. Explosive limits: 2.5% to 13% Miscible with water.

### Air transport

PCA Excepted quantities (IATA) : E2  
PCA Limited quantities (IATA) : Y341  
PCA limited quantity max net quantity (IATA) : 1L  
PCA packing instructions (IATA) : 353  
PCA max net quantity (IATA) : 5L  
CAO packing instructions (IATA) : 364  
CAO max net quantity (IATA) : 60L  
ERG code (IATA) : 3H

### Inland waterway transport

Classification code (ADN) : F1  
Limited quantities (ADN) : 1 L  
Excepted quantities (ADN) : E2  
Carriage permitted (ADN) : T  
Equipment required (ADN) : PP, EX, A  
Ventilation (ADN) : VE01  
Number of blue cones/lights (ADN) : 1

### Rail transport

Classification code (RID) : F1  
Limited quantities (RID) : 1L  
Excepted quantities (RID) : E2  
Packing instructions (RID) : P001, IBC02, R001  
Mixed packing provisions (RID) : MP19  
Portable tank and bulk container instructions (RID) : T4  
Portable tank and bulk container special provisions (RID) : TP1  
Tank codes for RID tanks (RID) : LGBF  
Transport category (RID) : 2  
Colis express (express parcels) (RID) : CE7  
Hazard identification number (RID) : 33

### 14.7. Maritime transport in bulk according to IMO instruments

Not applicable

# Graffiti Remover

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

##### 15.1.1. EU-Regulations

###### REACH Annex XVII (Restriction List)

Contains no REACH substances with Annex XVII restrictions

###### REACH Annex XIV (Authorisation List)

Contains no REACH Annex XIV substances

###### REACH Candidate List (SVHC)

Contains no substance on the REACH candidate list

###### PIC Regulation (Prior Informed Consent)

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

###### POP Regulation (Persistent Organic Pollutants)

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

###### Ozone Regulation (1005/2009)

Contains no substance subject to REGULATION (EU) No 1005/2009 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 September 2009 on substances that deplete the ozone layer.

###### Dual-Use Regulation (428/2009)

Contains no substance subject to the COUNCIL REGULATION (EC) No 428/2009 of 5 May 2009 setting up a Community regime for the control of exports, transfer, brokering and transit of dual-use items.

###### Explosives Precursors Regulation (2019/1148)

Contains substance subject to Regulation (EU) 2019/1148 of the European Parliament and of the Council of 20 June 2019 on the marketing and use of explosives precursors.

##### ANNEX II REPORTABLE EXPLOSIVES PRECURSORS

List of substances on their own or in mixtures or in substances for which suspicious transactions and significant disappearances and thefts are to be reported to the relevant national contact point within 24 hours.

Name	CAS-No.	Combined Nomenclature code (CN)	Combined Nomenclature code for mixture without constituents which would determine classification under another CN code
Acetone	67-64-1	2914 11 00	ex 3824 99 92

Please see [https://ec.europa.eu/home-affairs/system/files/2021-11/list\\_of\\_competent\\_authorities\\_and\\_national\\_contact\\_points\\_en.pdf](https://ec.europa.eu/home-affairs/system/files/2021-11/list_of_competent_authorities_and_national_contact_points_en.pdf)

###### Drug Precursors Regulation (273/2004)

Contains no substance subject to Regulation (EC) 273/2004 of the European Parliament and of the Council of 11 February 2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances.

##### 15.1.2. National regulations

###### France

Occupational diseases	
Code	Description
RG 84	Conditions caused by liquid organic solvents for professional use: saturated or unsaturated aliphatic or cyclic liquid hydrocarbons and mixtures thereof; liquid halogenated hydrocarbons; nitrated derivatives of aliphatic hydrocarbons; alcohols; glycols, glycol ethers; ketones; aldehydes; aliphatic and cyclic ethers, including tetrahydrofuran; esters; dimethylformamide and dimethylacetamine; acetonitrile and propionitrile; pyridine; dimethylsulfone and dimethylsulfoxide



# Graffiti Remover

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### Germany

- Employment restrictions : Observe restrictions according Act on the Protection of Working Mothers (MuSchG).  
Observe restrictions according Act on the Protection of Young People in Employment (JArbSchG).
- Water hazard class (WGK) : WGK 3, Highly hazardous to water (Classification according to AwSV, Annex 1).
- Hazardous Incident Ordinance (12. BImSchV) : Is not subject of the Hazardous Incident Ordinance (12. BImSchV)

### Netherlands

- SZW-lijst van kankerverwekkende stoffen : None of the components are listed
- SZW-lijst van mutagene stoffen : None of the components are listed
- SZW-lijst van reprotoxische stoffen – Borstvoeding : None of the components are listed
- SZW-lijst van reprotoxische stoffen – Vruchtbaarheid : None of the components are listed
- SZW-lijst van reprotoxische stoffen – Ontwikkeling : None of the components are listed

### Denmark

- Classification remarks : Emergency management guidelines for the storage of flammable liquids must be followed
- Danish National Regulations : Young people below the age of 18 years are not allowed to use the product  
Pregnant/breastfeeding women working with the product must not be in direct contact with the product

## 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

## SECTION 16: Other information

### Abbreviations and acronyms:

ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration

# Graffiti Remover

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Abbreviations and acronyms:	
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disrupting properties

Full text of H- and EUH-statements:	
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.